



TIPS & TRICKS

Pipe Linux command output to the Web in real-time

If you want to share your Linux command output to your support team or colleagues, instead of sharing your screen with them, you can use 'Seashells' to pipe out the output to a website. It can also be used as a monitoring tool for long-running processes that are continuously producing an output in the console. There is no need to install any software for this, as 'Seashells' uses Netcat which comes preinstalled on most systems. Here is how it works:

```
$ echo 'Hello, OpenSourceForU !' | nc seashells.io 1337  
serving at https://seashells.io/v/{random url}
```

If you like it and want to use it frequently, then you can install the Seashells client by running the following command:

```
pip install seashells
```

Once you have the client installed, then you can directly output to 'seashells' instead of 'nc seashells.io 1337'. The client gives you additional features and to find out more about it, run 'seashells --help'.

Here is an example:

```
$ python myThread.py | seashells  
serving at https://seashells.io/v/{url}  
{Output of your program}
```

```
$ top | seashells  
serving at https://seashells.io/v/{url}  
{Output of top command}
```

—Rushikesh Gaidhani, rushi.rg@gmail.com

Sharing files from the terminal with users present in the same network

If two users who are on the same network want to share data between them, they can type the following commands

in the terminal:

Receiver:

```
nc -l <port> > filename
```

```
$nc -l 2044 testfile
```

After typing the above command, hit 'Enter' and wait. The receiver has the IP address as 192.168.0.2

Sender:

```
nc <ip address of receiver> <port> < <filepath/filename>  
$nc 192.168.0.2 2044 < /home/test/testfile
```

This way, both can exchange data without using any external storage device.



Note: Sender and Receiver should use the same port number while transferring data; Receiver should first hit 'Enter' and wait before Sender hits 'Enter'.

—Anirudh kalwa, anirudh.3194@gmail.com



Resolving configuration issues in LibreOffice

Here is a simple tip that will help resolve issues that often arise after the upgradation of LibreOffice on a Linux based system. These issues are due to bad profile configurations. Given below is the command that will resolve such issues, by creating a new set of configurations.

All you need to do is to rename the profile folder using the following command in the Linux terminal:

```
$ cd ~/.config && mv libreoffice libreoffice.old
```

Now, whenever you start LibreOffice, a new set of profile configurations will be created automatically.

—Amit Doegar, amit@nitrchd.ac.in