

which are made of two parts — the object type (user, group, etc) and the operation that performs on that object (add, del, find, etc). Get a list of those sub-commands with *ipa help commands*.

```
# ipa help commands
```

- For example, to create a user, we would look to use the sub-command of *user-add*. But to find the additional operation, use the following command:

```
# ipa help user-add
```

...to create a user interactively.

We never set the password, to use the sub-command *user-mod*:

```
# ipa user-mod user1 --password
```

Confirm the user exists with the command *ipa user-find*.

Add a second user *linux user2* with no prompting and a random password:



Figure 3: Verifying Kerberos' authentication and IPA access



Figure 4: Log in to the IdM domain to obtain a Kerberos ticket



Figure 5: A user named *linux user1* is created and the password is assigned by the *user-mod* command

```
# ipa user-add user2 --first=linux --last=user2 --random
```

- Create a group, putting the previous two users in the group. To create a group, use the command *group-add*:

```
# ipa group-add group1
```

To add both members in the group, use the following command:

```
# ipa group-add-member group1 --users user1,user2
```

To verify the group, use the following command:

```
# ipa group-find group1
```

Note: Recall that the first time you log in or authenticate with *kinit*, you will be prompted to change your password. While this is not shown above, just follow the prompts and be sure to note the new password.

- Now begin to explore the Web based administrative interface. Navigate to <https://demo.example.com>, which will display the message 'This connection is untrusted'. Choose 'I Understand the Risks', then 'Add an Exception' and 'Confirm Security Exceptions'. After accepting the certificate from the Identity Management server, we need to configure Firefox to use Kerberos for its credentials. If this is the first time



Figure 6: *User-find* command confirms existence of two users -- *admin* and *linux user2*




Figure 7: User added *linux user2* with random password