

you are connecting, you will be prompted to do this. Of course, this assumes that you have already run *init* and have your ticket. Choose 'Firefox Configuration Page'. Then select the 'Import Certificate Authority' certificate. Select all three check boxes, before clicking on 'OK'. Choose 'Proceed to configuration page for older versions of Firefox'. Under 'Automatic configuration of older versions', click on 'Configure Firefox', and then on 'Allow'. Finally, choose 'Click here to return to Web UI'.

- Notice the three basic tabs — Identity, Policy and IPA Server. The first tab, Identity, has configuration areas to define each of the entities in the database — users, user groups, hosts, host groups, net groups, services, and DNS records, if enabled. The second tab, Policy, has configuration areas for host based access control (HBAC), sudo rules, automount, user password policy, Kerberos ticket policies, SELinux user maps, and automember. The final tab, IPA Server, has configuration areas for role based access control (RBAC), self-service permissions, delegations, ID ranges, trusts and configuration.
- To create another user, click on 'Add'. Next, enter the details of the user, and click on 'Add User'. Then click on 'Add' again (Figure 8).

Registering a client system with IdM

- Perform the prerequisite steps by opening the necessary ports in the firewall. System ports for IdM services include HTTP/HTTPS (80/tcp and 443/tcp), LDAP/LDAPS (389/tcp and 636/tcp), Kerberos (88 and 464, both tcp and udp), DNS (53, both tcp and udp), NTP(123/udp), and Certificate System (7389/tcp). The above ports must be opened. If the IdM server was configured as the DNS server, ensure that the client machine points to the IdM server first for DNS by making it the first entry in */etc/resolv.conf*.
- Install IdM client packages. Installing *ipa-client* will typically install a number of dependencies. If the IdM client also functions as an administrator machine, then you must install one additional package — *ipa-admintools*, as follows:

```
# yum -y install ipa-client ipa-admintools.
```

- Enrol your client system as a client of the earlier created IdM server, *server.example.com*, in the domain using the credentials of the admin and passphrase, enabling the PAM home directory modules. Like some of the options with *ipa-server-install*, the *--mkhomedir* option must be specified on the command line since it is not a question asked interactively. The same result could be achieved by passing the following arguments to the *ipa-client-install* command.




Figure 8: Both *linux user1* and *linux user2* are added in the new group



Figure 9: Shown here are three basic tabs and previously created users — *user1* and *user2*



Figure 10: How to enrol you client machine to an earlier created IdM server

```
#ipa-client-install --domain=xyz.com --server=demo.example.com --realm=EXAMPLE.COM -p admin -w linux123 --mkhomedir -U.
```

- Confirm successful configuration by testing the lookup information of the standard user admin and group admins.
- In preparation for the end of our practical session, and to prevent conflicting database information, we need to cleanly remove this client system's enrolment in the domain.

```
#ipa-client-install -uninstall
```

After the machine completes the reboot, remove the CA certificate from the client machine.

```
#rm -rf /etc/ipa/ca.crt. END
```

By: Kshitij Upadhyay

The author is RHCSA and RHCE certified, and loves to write about new technologies. He can be reached at upadhyayk04@gmail.com.