

folder, which contains access information for each node:

```
[nodes]
as1 ansible_host=10.0.0.11 ansible_connection=ssh ansible_
user=vagrant ansible_ssh_private_key_file=~/.vagrant.d/
insecure_private_key
as2 ansible_host=10.0.0.12 ansible_connection=ssh ansible_
user=vagrant ansible_ssh_private_key_file=~/.vagrant.d/
insecure_private_key
as3 ansible_host=10.0.0.13 ansible_connection=ssh ansible_
user=vagrant ansible_ssh_private_key_file=~/.vagrant.d/
insecure_private_key
```

We also create `inventory/vbox/group_vars/all/all.yml` with the following variables:

```
---
aerospike_edition: "community"
aerospike_version: "latest"

amc_version: 3.6.13
```

Installing Aerospike

The entire set of playbooks is available in the `playbooks/configuration/aerospike.yml` file. The first step is to install the Aerospike server on all the three nodes using Ansible, as shown below:

```
---
- name: Configure Aerospike cluster node
  hosts: nodes
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [server]

tasks:
  - name: Create downloads directory
    file: path="/home/{{ ansible_user }}/downloads"
    state=directory

  - name: Create installs directory
    file: path="/home/{{ ansible_user }}/installs"
    state=directory

  - name: Download Aerospike community server (RPM)
    get_url: url="http://aerospike.com/download/server/{{
aerospike_version }}/artifact/el6" dest="/home/{{ ansible_
user }}/downloads/"
    register: __community_server_file

  - set_fact:
    server_version: "{{ __community_server_file.dest |
basename }}"
```

```
- name: Extract Aerospike server
  command: tar xzvf "/home/{{ ansible_user }}/downloads/{{
server_version }}" -C installs

- name: Yum update
  yum: name=* update_cache=yes state=present

- name: Install RPM dependencies
  become: yes
  become_method: sudo
  yum:
    name: "[{{ item }}"
    state: latest
  with_items:
    - python
    - libselinux-python

- name: Run asinstall
  shell: cd "/home/{{ ansible_user }}/installs/{{ server_
version | regex_replace('\.tgz', '') }}" && sudo ./asinstall

- name: Start Aerospike server (RPM)
  shell: sudo service aerospike start

- name: Wait for server to be up and running
  wait_for:
    port: 3000
    delay: 5
    state: started
```

The `'downloads'` and `'installs'` directories are first created. The Aerospike server package for CentOS 6 is then downloaded and extracted. The `YUM update` command is used to update the software repository, following which the dependencies and the Aerospike server are installed. The database server is then started, and the playbook waits for the server to listen on port 3000. The above playbook can be run as follows:

```
$ ansible-playbook -i inventory/vbox/inventory playbooks/
configuration/aerospike.yml --tags server
```

Setting up a multicast cluster

The Aerospike cluster can be set up either in multi-cast or mesh mode. The following playbook configures the cluster in multicast mode:

```
- name: Create multicast cluster
  hosts: nodes
  gather_facts: true
  sudo: yes
  tags: [multicast]

vars:
```