

```

ip_address: "{{ ansible_eth1['ipv4']['address'] }}"
line_address: "          address {{ ip_address }}"

tasks:
- name: Stop aerospike server
  command: service aerospike stop

- name: Specify multicast configuration file parameters
  lineinfile:
    dest: /etc/aerospike/aerospike.conf
    insertafter: "{{ item.insertafter }}"
    line: "{{ item.line }}"
    state: present
  with_items:
    - { insertafter: 'proto-fd-max 15000', line: "
node-id-interface eth1" }
    - { insertafter: 'port 9918', line: "{{ line_address
}}" }
    - { insertafter: 'fabric', line: "{{ line_address }}" #
Multicast: Specify private IP address" }

- name: Update network service address
  replace:
    name: /etc/aerospike/aerospike.conf
    regexp: 'address any'
    replace: "address {{ ansible_eth1['ipv4']['address']
}}"

- name: Start aerospike server
  command: service aerospike start

```

The above playbook can be executed using the following command:

```
$ ansible-playbook -i inventory/vbox/inventory playbooks/
configuration/aerospike.yml --tags multicast
```

You can verify the multi-cast cluster setup by logging into one of the virtual machines, and using the Aerospike Admin (asadm) tool as illustrated below:

```

[vagrant@as1 ~]$ asadm
Aerospike Interactive Shell, version 0.1.15

Found 3 nodes
Online: 10.0.0.11:3000, 10.0.0.13:3000, 10.0.0.12:3000

Admin> exit
[vagrant@as1 ~]$

```

Installing the Aerospike Management Console

The Aerospike Management Console (AMC) dashboard provides a graphical user interface (GUI) for the Aerospike server. Its installation playbook is as follows:

```

- name: Install Aerospike Management Console
  hosts: nodes
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [amc]

tasks:
- name: Download AMC Community RPM package
  get_url: url="http://www.aerospike.com/download/amc/{{
amc_version }}/artifact/el6" dest="/home/{{ ansible_user }}/
downloads/"
  register: __community_amc_file

- set_fact:
  amc_file: "{{ __community_amc_file.dest }}"

- name: Install RPM dependencies
  yum:
    name: "{{ item }}"
    state: latest
  with_items:
    - gcc
    - python-devel

- name: Install RPM amc
  command: rpm -ivh "{{ amc_file }}"

- name: Start AMC server (RPM)
  shell: sudo service amc start

```

The invocation of the above playbook and a sample execution run is shown below:

```

$ ansible-playbook -i inventory/vbox/inventory playbooks/
configuration/aerospike.yml --tags amc
PLAY [Configure Aerospike cluster node] *****
TASK [setup] *****
ok: [as2]
ok: [as1]
ok: [as3]

PLAY [Create multicast cluster] *****

TASK [setup] *****
ok: [as1]
ok: [as2]
ok: [as3]

PLAY [Install Aerospike Management Console] *****
TASK [setup] *****
ok: [as1]
ok: [as2]
ok: [as3]

```