

```

TASK [Download AMC Community RPM package] *****
changed: [as2]
changed: [as1]
changed: [as3]

TASK [set_fact] *****
ok: [as1]
ok: [as2]
ok: [as3]

TASK [Install RPM dependencies] *****
changed: [as1] => (item=[u'gcc', u'python-devel'])
changed: [as2] => (item=[u'gcc', u'python-devel'])
changed: [as3] => (item=[u'gcc', u'python-devel'])

TASK [Install RPM amc] *****
changed: [as1]
changed: [as2]
changed: [as3]

TASK [Start AMC server (RPM)] *****
changed: [as1]
changed: [as2]
changed: [as3]

PLAY RECAP *****
as1      : ok=8    changed=4    unreachable=0    failed=0
as2      : ok=8    changed=4    unreachable=0    failed=0
as3      : ok=8    changed=4    unreachable=0    failed=0

```

You can now open <http://10.0.0.1:8081> in a browser on the host system, and you will be prompted with a modal window, as shown in Figure 1.

You can input 'localhost' for the 'Host Name', and the AMC dashboard opens as shown in Figure 2.

Uninstalling Aerospike

An uninstall playbook is written to stop the services, and uninstalls both the Aerospike Management Console (AMC) and the Aerospike server, as follows:

```

- name: Uninstall
  hosts: nodes
  become: yes
  become_method: sudo
  gather_facts: true
  tags: [uninstall]

tasks:
  - name: Stop AMC server
    service:
      name: amc
      state: stopped

```




Figure 1: AMC modal window




Figure 2: AMC dashboard

- name: Uninstall RPM AMC
command: yum remove aerospike-amc-* -y
- name: Stop server
command: service aerospike stop
- name: Uninstall server
shell: yum remove aerospike-* -y

The above playbook can be run using the following command:

```
$ ansible-playbook -i inventory/vbox/inventory playbooks/
configuration/aerospike.yml --tags uninstall
```

You can read the documentation at <https://www.aerospike.com/docs/> to learn more about Aerospike. 

By: Shakthi Kannan

The author is a free software enthusiast and blogs at shakthimaan.com.