

```
...
...

column_name2 column_data_type,
);
```

Let us create a table to store student information, as follows:

```
testdb=# CREATE TABLE student_table (

    id            SMALLINT,
    name          VARCHAR(32),
    age           SMALLINT,
    address       VARCHAR(128),
    department    VARCHAR(128)
);
```

To list a table, use the *psql* command as follows:

```
testdb=# \d
```

We can use the *DROP TABLE* statement to remove a table and its data from the database permanently. The syntax is as follows:

```
DROP TABLE table_name;
```

For instance, to drop *student_table*, execute the command given below:

```
testdb=# DROP TABLE student_table;
```

We can use the *ALTER TABLE* statement to update table properties, like its name, columns, data type and so on. To rename a table, use the *RENAME TO* statement as follows:

```
testdb=# ALTER TABLE student_table RENAME TO new_student_
table;
```

To remove a column from the table definition, use the *DROP COLUMN* statement as follows:

```
testdb=# ALTER TABLE student_table DROP COLUMN AGE;
```

To add a new column to the table definition, use the *ADD COLUMN* statement as follows:

```
testdb=# ALTER TABLE student_table ADD COLUMN AGE SMALLINT;
```

To remove all data from a table, use the *TRUNCATE TABLE* statement as follows:

```
testdb=# TRUNCATE TABLE student_table;
```

Working with rows

We can use the *INSERT INTO* statement to insert data into a table. Its syntax is as follows:

```
INSERT INTO table_name (column1, column2, ... columnN)
VALUE(value1, value2, ... valueN);
```

For instance, the statement below inserts a new row into the table:

```
testdb=# INSERT INTO student_table (id, name, age, address,
department) VALUES(1
, 'Jarvis', 21, 'Earth', 'CS');
```

To update an existing record, use the *UPDATE* statement. Its syntax is as follows:

```
UPDATE table_name
SET column1 = value1, column2 = value2..., columnN = valueN
WHERE [condition];
```

For instance, the statement below updates the age of the student whose ID is '1':

```
testdb=# UPDATE student_table
SET age=22
WHERE id=1;
```

To delete a record, we can use the *DELETE FROM* statement. Its syntax is as follows:

```
DELETE FROM table_name
where [condition];
```

For instance, the statement below deletes the row with the ID '1':

```
testdb=# DELETE FROM student_table WHERE id=1;
```

Querying data

We can use the *SELECT* statement to query data from the table. Its syntax is as follows:

```
SELECT column1, column2 ... columnN FROM table_name
WHERE [condition];
```

For instance, the statement below lists the names of the students aged '21':

```
testdb=# SELECT name FROM student_table WHERE age=21;
```

We can use the *ORDER BY* clause to sort records. To sort by ascending order, we have to use the *ASC* keyword and to sort by descending order, we have to use the *DESC* keyword.