

directory. In the directory of RethinkDB, there is a file called *rethinkdb.exe*. On double-clicking it, the server gets initiated and is then available for further database operations.

After starting the RethinkDB server, the administration console needs to be opened on the Web browser with the URL <http://127.0.0.1:8080>, so that different options can be viewed for database administration.

The options for creating the database and tables with different privileges are available in the administrative panel of the RethinkDB server. The connected servers, tables, indexes and resources can be viewed in the panel, as shown in Figure 3.

To use a specific directory for the storage and logging of data, the following instruction is used:

```
WindowsDirectory:>rethinkdb.exe -d c:\RethinkDB\data\
```

To specify a particular server name and cluster, use the command given below:

```
WindowsDirectory:>rethinkdb.exe -n MyDomain -j mycluster.  
server.com
```

In the administrative console, there is the option to create a new database with any name. This database name can be called in the front-end applications for real-time applications.

Once the database is created, it is visible in the administration console. In a similar way, the table in a particular database can be created with the specification of a primary key, along with the acknowledgement.

After creating the table in a specific database, the



Figure 4: Creating a new database




Figure 5: View the database after creation




Figure 6: Adding a table in a specific database



Figure 7: Returned message after creating a table on the dashboard of RethinkDB

RethinkDB engine returns the message in JSON format so that the confirmation of the write operation can be displayed with different values inserted in the database table.

Installing RethinkDB on Ubuntu

For the installation of RethinkDB on Ubuntu Linux, both 32-bit and 64-bit flavours are available.

```
$ source /etc/lsb-release && echo "deb http://download.  
rethinkdb.com/apt $DISTRIB_CODENAME main" | sudo tee /etc/  
apt/sources.list.d/rethinkdb.list  
$ wget -qO- https://download.rethinkdb.com/apt/pubkey.gpg |  
sudo apt-key add -  
$ sudo apt-get update  
$ sudo apt-get install rethinkdb
```

Compilation and installation from source

To compile and install from the source, use the following commands: