



Figure 1: CUBRID's features



Figure 2: CUBRID's enterprise features




Figure 3: Getting started with CUBRID

Step 3: Once the CUBRID service is started, you can create and start using the databases. Two sample commands are shown below:

```
cubrid createdb osfytst en_US
cubrid server start osfytst
```

Step 4: The next step is to connect to the database using CSQL. The command for doing that is as follows:

```
csql -user PUBLIC osfytst
```

Step 5: After the completion of all the above steps, you can run the required SQL queries.

CUBRID vs MySQL

As MySQL is a leading open source database management system (DBMS), you may get asked about their relative merits. First and foremost, CUBRID is not derived from MySQL. It is a separate RDBMS tool which has around 20

years of development history, as mentioned earlier.

Regarding performance, the official CUBRID documentation claims that it is faster than MySQL in scenarios when there are many concurrent requests. Unlike some other RDBMSs, CUBRID has no separate enterprise licence. It has only one flavour, which is under GPL version 2 or higher. Hence, CUBRID is completely free with all its enterprise level features.

CUBRID language support

CUBRID supports many popular programming languages. It does so by providing language-specific APIs (Application Programming Interfaces). CUBRID is written in C and hence there is a native C driver. This driver is referred to as CCI. Apart from this, CUBRID has support for the following programming languages:

- Java
 - PHP
 - Ruby
 - Python
 - Perl
 - Node.js
 - ADO.NET driver for .NET programming languages
- In this article, examples with two popular programming languages — Java and Python — are given.

A simple CUBRID example with Java

This section introduces you to a compact and standalone Java program that interacts with CUBRID. For this program to work, you should have already installed CUBRID, having followed the steps mentioned earlier, and it requires the JDBC driver as well. If your system doesn't have it, then do install it. The installer is available at <https://www.cubrid.org/downloads/os-select/64-bit/drivers/jdbc-->

```
package org.cubrid.demo;
import java.sql.Connection;
import java.sql.ResultSet;
import java.sql.Statement;
import static java.sql.DriverManager.getConnection;
public class Main {
    public static void main(String[] args) {
        String url = "jdbc:cubrid:localhost:33000:demo:publ
ic::?charset=utf8";
        try {
            Class.forName("cubrid.jdbc.driver.CUBRIDDriver");
            Connection conn = getConnection(url, null, null);
            conn.setAutoCommit(false);
            try (Statement stmt = conn.createStatement()) {
                // Create a new table and insert some data
                stmt.execute("drop table if exists mytable");
                stmt.execute("create table mytable(mycolumn
string)");
                stmt.execute("insert into mytable values('This is
```