

Figure 2: Goaccess dashboard

from the terminal for the Nginx *access.log* file as follows:

```
$ sudo goaccess -f /var/log/nginx/access.log -p ~/.goaccessrc -a
```

You will see the Goaccess dashboard as illustrated in Figure 2.

You can also export the dashboard to an HTML report that you can view in a browser:

Figure 3: Goaccess HTML report

```
$ sudo goaccess -f /var/log/nginx/access.log -p ~/.goaccessrc
-a > report.html
```

A sample screenshot of the HTML report is shown in Figure 3.

You are encouraged to read the Goaccess manual page at *https://goaccess.io/man* to learn more about its usage. END

By: Shakthi Kannan

The author is a free software enthusiast and blogs at *shakthimaan.com*.

Continued from page no...35

more task-specific ones such as daemon- and user-specific volatile directories under */run*. In this context, 'volatile' means that the file system storing these files only exists in memory. When the system reboots or loses power, all the contents of volatile storage will be gone.

To keep a system running cleanly, it is necessary for these directories and files to be created when they do not exist (since daemons and scripts might rely on them being there), and for old files to be purged so that they do not fill up disk space or provide fault-configured directories.

In RHEL 7, *systemd* provides a more structured and configurable method to manage temporary directories and files: *system-tmpfiles*.

When the system starts, one of the first service units launched is *system-tmpfiles-setup*. This service runs the command *system-tmpfiles –create –remove*. This command reads configuration files from */usr/lib/tmpfiles.d/*.conf*, */run/tmpfiles.d/*.conf*, and */etc/tmpfiles.d/*.conf*. Any files and directories marked for deletion in those configuration files will be removed, and any files and directories marked for creation (or permission fixes) will be created with the correct permissions, if necessary.

Regular checking

To make sure that long running systems do not fill up their disks with stale data, there is also a *sytemd* timer unit that calls *system-tmpfiles –clean* at a regular interval.

systemd timer units are a special type of *systemd* service that have a *{TIMER}* block indicating how often the service with the same name should be started.

On a RHEL 7 system, the configuration for the *systemd-tmpfiles-clean.timer* units looks like what is shown below:

```
[Timer]
OnBootSec=15min
OnUnitActiveSec=1d
```

This indicates that the service with the same name (*systemd-tmpfiles-clean.service*) will be started 15 minutes after *systemd* has started and then once every 24 hours, afterwards.

The command *systemd-tmpfiles --clean* parses the same configuration files as *systemd-tmpfiles –create*, but instead of creating files and directories, it will purge all files that have not been accessed, changed or modified till the maximum age defined in the configuration file. END

By: Kshitij Upadhyay

The author is RHCSA and RHCE certified, and loves to write about new technologies. He can be reached at *upadhyayk04@gmail.com*.