



TIPS & TRICKS

Converting a CSV file to a DSV file using the *column* and *cat* commands

To understand how to convert a CSV file to a DSV file, let's look at a few examples of ESS.csv.

ESS.csv is a comma-separated file; its left and right enclosure is "" and the field separator is ','.

Example 1: To convert the ESS.csv file to a delimited file (i.e., dsv) using the *column* command, try the following command:

```
cat ESS.csv | column -t -s '""' -o "" | column -t -s ',' -o ',' > ESS.dsv
```

The above command changes the left and right enclosures from "" to none and the field separator is ','.

You can customise the left enclosure as per your requirements.

Example 2: Change the left and right enclosures from "" to '' and the field separator is ','.

```
cat ESS.csv | column -t -s '""' -o "" | column -t -s ',' -o ',' > ESS.dsv
```

Example 3: Change the left and right enclosures from "" to ':' and the field separator is ','.

```
cat ES.csv | column -t -s ':' -o ':' | column -t -s ',' -o ',' > ES.dsv
```

Example files are available on GitHub at <https://github.com/hemanth22/CSVToCustomDSV> and at the GitHub Wiki guide <https://github.com/hemanth22/CSVToCustomDSV/wiki/Guide-to-use-CSVToCustomDSV>.

To download an example, use the following command:

```
git clone https://github.com/hemanth22/CSVToCustomDSV.git
```

—Hemanth Bitra,
hemanthbitra@bitroid.in



Resetting a forgotten root user account password in CentOS 7/RHEL

We can easily reset the root user account by booting into the single mode using the following steps.

Step 1: While booting the system, you see a screen with two options as shown below:

```
CentOS Linux, with Linux 3.10.0-123.el7.x86_64
CentOS Linux, with Linux 0-rescue-27ca624e1d5b47ad97bba2bbc648d347
```

Use the arrow keys as soon as you see the screen with the above two options so that a time-out does not take place. Now select the first option and press the 'e' key to edit.

Step 2: You will be presented with the kernel parameters' screen, and you may have to use the arrow key to see the line where the 'vmlinuz' mount point is set. Here, search for the text 'rhgb quiet' and replace this text with 'init=/bin/bash' without quotes, and press *Control+x* to boot the system with this edited configuration.

Step 3: After booting, you will see what's shown below:

```
bash-4.2#
```