

You will directly get the bash shell with root privileges where you can reset the root password using the 'passwd' command as shown below:

```
bash-4.2# passwd
```

You can successfully reset the root account password in this way.

—Sharmin Shaikh,
imsharmeen@gmail.com



Never miss the Ubuntu notification 'system restart required'

We must reboot the server when we install a new kernel or libraries. Ubuntu Linux can tell you if the system needs a reboot when you login as root user.

```
*** System restart required ***
```

The above warning will appear on the login screen, but we may miss this warning. So here is the simple script for administrators to find out exactly when the system requires a reboot.

You can manually find the file /var/run/reboot-required, which indicates that a system restart is required.

Instead of a manual search, you can use the following script to identify the Ubuntu notification of 'system restart required' at every login and never miss the warning.

Add the following lines in the file /root/status.sh:

```
#!/bin/bash
if [ -f /var/run/reboot-required ]
then
    echo -e "33[33;31m*** Hello $USER, you must reboot
your machine ***33[0m"
else
    echo -e "33[33;32m*** System reboot is NOT required
now ***\n"cat /var/lib/update-notifier/updates-available\`
n33[0m"
fi
```

Now we can add the file path /root/status.sh in /root/.bashrc file to check for the 'Reboot required' task at every login made by the root user.

```
# echo "/root/status.sh" >> /root/.bashrc && tail -n3 /
root/.bashrc
```

—Ranjithkumar T,
ranjith.stc@gmail.com



Multiple tips for daily use

1. Copy from or paste into the terminal in Ubuntu

Many people try to paste into the terminal by using Ctrl+v. But this will not work. We need to use Ctrl+Shift+v to paste into the terminal. Similarly, to copy from the terminal, select the text to be copied and use Ctrl+Shift+c.

This is the simplest and easiest way for new users to overcome the problems of copying and pasting into the terminal.

2. Using 'tac' to output the contents of a file instead of 'cat'

Many people use the 'cat' command to output the contents on the terminal. If the contents are huge, then users have to scroll up till they reach the first line of the content. Instead of scrolling all the way up till the beginning and scanning, users can replace 'cat' with 'tac'. The latter works just like the 'cat' command — the only difference is that the results are printed in reverse order; i.e., the first line comes last and the last line appears first. So users can easily see the first line without scrolling all the way to the beginning.

3. Getting to know the permissions of files using the 'ls-l' command on the terminal in Ubuntu

One can get to know the permission of any file in the system by executing the 'ls-l' command on the terminal. The permissions are shown in the first column. r-read, w-write and x-execute are permissions for different users, i.e., the first three characters are to show permissions of the owner on that file, the next three are for group permissions and the last three are for others' permissions on that file. There will be an initial '-' before listing permissions of that file. So users can get to know who all can access the file that they themselves are using or going to.

As an example, -rwxrw-r-- tells us that there is read, write and execute permissions for the owner; read and write permissions for the group; and only read permission for others, on the file.

—Anirudh Kahwa,
anirudh.3194@gmail.com



Share Your Open Source Recipes!

The joy of using open source software is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in OSFY so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.