

file, use the following commands:

```
#cat /tmp/test.txt
name1
name2
foldername/name3
...
nameN
foldernameN
```

```
#for i in $(cat /tmp/test.txt);do du -sh $i; done
```

—Remin Raphael, remin13@gmail.com



A command line hack for crontab

This small script installs itself in crontab if the script is already not there.

I had a script [/tmp/script.sh] that I needed to run in crontab, but as it was under development, every now and then the version got updated, and I had to recopy the script and add it.

The following script helped me a lot.

```
#crontab -l | grep -q 'bash /tmp/script.sh' && \
echo "exists" || cat <(crontab -l) \
<(echo "0 */2 * * * bash /tmp/script.sh") | crontab -"
```

You can modify this simple script to suit your needs.

—Murali Sridhar, muralesridhar@gmail.com



How to find a file larger than 1GB, 100MB or any size

We often need to get the listing of a directory and fetch files that are bigger than, say, 1GB or 100MB. Here's a tip that you can use for this. Run the following commands with root access.

* For file sizes of 1GB or more, use the command:

```
#sudo find / -xdev -type f -size +1G -exec ls -lh {} \;
```

* For file sizes of 100MB or more, give the following command:

```
#sudo find / -xdev -type f -size +100M -exec ls -lh {} \;
```

—Rupin Puthukudi, rupinmp@gmail.com



Disabling the touchscreen in Ubuntu

Many of the latest laptops come with a touchscreen. Sometimes we need to disable or enable the touch facility for a particular purpose.

Here is a command that will help you to do that, if you are using Ubuntu:

```
Sxinput set-prop 10 'Device Enabled' 0
```

For enabling the touchscreen, type:

```
xinput set-prop 10 'Device Enabled' 1
```

—Sethu Ram, dycmiti@konkanrailway.com



How to change a user's password in a non-interactive way

If you want to change a password without prompting for it, say, in scripts, use the following command:

```
$ sudo echo -e "password\npassword" | passwd testuser
```

—Krishna Murthy Thimmaiah, gtk321@rediffmail.com



Increase the size of your 'history'

The 'history' command displays a list of the previous commands you used on the terminal. By default, it stores only the last 1000 commands that you used. Often, we need to store more than 1000 commands. To enable this, we need to change the following lines in the '.bashrc' file in the home folder.

To open the '.bashrc' file, use the following command in the terminal:

```
$vi ~/.bashrc
```

...and change the following two lines:

```
HISTSIZE=1000
HISTFILESIZE=2000
```

For instance, if you want to increase your history size to 40000, then these two lines should be:

```
HISTSIZE=40000
HISTFILESIZE=40000
```

Now, save the file.

—Nagaraju Dhulipalla, nagarajunice@gmail.com



Share Your Linux Recipes!

The joy of using Linux is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.