

```
rabbitmq-server (none) (none)
nodejs Fedora Project Fedora Project
mongodb-org-mongos (none) (none)
pbs Altair Engineering, Inc (none)
npm Fedora Project Fedora Project
gpg-pubkey (none) (none)
uwsgi Fedora Project Fedora Project
[root@blrvvmXXvmXX ~]#
```

In the above command, you have:

```
%{NAME} --> package name
%{VENDOR} --> vendor name
%{DISTRIBUTION} --> distribution name
```

—Bhagyaraj M.C.,
bhagym@india.altair.com

Unfreeze your Linux terminal from accidental **Ctrl+S**

If you use Windows regularly and are new to Linux, then you probably opt for **Ctrl+S** to save your data. But if you use that in Linux, you'll have a frozen terminal.

Don't worry, you no longer have to close the terminal. Just use **Ctrl+Q** and you can use the terminal again.

—Neetesh Mehrotra,
mehrotra.neetesh@gmail.com

Ping multiple IPs simultaneously

It is really a painful task to ping a bunch of IPs, one after another. The following command will help you to ping a group of IPs, simultaneously.

Just collect the IP list/host name into the file (say, *ip_file*) and execute the following command. If the host names are provided, then make sure these names resolve their respective IPs.

Open a text editor and create a file with the IP address or host name. Save the file as *ip_file*:

```
#cat ip_file
192.168.10.10
comp01
comp02
comp03
comp04
comp05
comp06
```

Now execute the following command:

```
#cat ip_file | xargs -P 0 -n1 -ihost bash -c 'ping -q
```

```
-W 1 -c 4 host &> /dev/null && echo host passed || echo
host failed'
```

```
192.168.10.10 passed
comp01 passed
comp02 passed
comp03 passed
comp04 passed
comp05 failed
comp06 passed
```

This will surely reduce your daily tasks and save some valuable time.

—Prasanta Behera,
mymail8500@gmail.com

Create and switch to a new branch in Git

It is often convenient to start development on a new branch. With a centralised version control system, a new branch is an expensive operation. However, with Git, this can be done very fast. We can create and switch to a new branch using just a single Git command as follows:

```
$ git checkout -b new-branch
```

This switches you to a new branch, called 'new-branch'.

—Narendra Kangralkar,
narendra0002017@gmail.com

Errata

The tip 'Emptying a file without deleting and renaming it again' published in the August 2018 issue of *OSFY* was submitted by Arsh Sharma, arshsharma25@gmail.com.



Share Your Open Source Recipes!

The joy of using open source software is in finding ways to get around problems—take them head on, defeat them! We invite you to share your tips and tricks with us for publication in *OSFY* so that they can reach a wider audience. Your tips could be related to administration, programming, troubleshooting or general tweaking. Submit them at www.opensourceforu.com. The sender of each published tip will get a T-shirt.