

```
gpgcheck=0
enabled=1
```

The Ansible playbook for setting up the pre-requisite repositories is given below:

```
---

- name: Repository setup
  hosts: sensu
  become: yes
  become_method: sudo
  gather_facts: yes
  tags: [repo]

tasks:
  - name: Install epel-release
    yum:
      name: epel-release
      state: present

  - name: Create sensu.repo
    copy:
      src: ../../files/sensu.repo
      dest: /etc/yum.repos.d/sensu.repo
```

The above playbook can be invoked using the following command:

```
$ ansible-playbook -i inventory/kvm/
inventory playbooks/configuration/sensu.
yaml --tags repo -vv -K
```

The -vv represents the verbosity in the Ansible output. You can use up to four v's for a more detailed output. The -K option prompts for the sudo password for the centos user account.

Redis

The Redis in-memory database is used as a data store and for transport. You can install it using the YUM tool. In the following example, the protected-mode in Redis configuration is disabled as we are in development mode and the server is started. We wait for the Redis server to run on port 6379. The Ansible playbook for installing, configuring and starting Redis is as follows:

```
- name: Install Redis
```

```
hosts: sensu
become: yes
become_method: sudo
gather_facts: true
tags: [redis]

tasks:
  - name: Install Redis
    yum:
      name: redis
      state: present

  - lineinfile:
      path: /etc/redis.conf
      regexp: '^protected-mode yes'
      line: 'protected-mode no'

  - name: Start Redis
    systemd:
      name: redis
      state: started

  - wait_for:
      port: 6379
```

The above playbook can be executed as follows:

```
$ ansible-playbook -i inventory/kvm/
inventory playbooks/configuration/sensu.
yaml --tags redis -vv -K
```

Sensu

You can now proceed to install Sensu and the Uchiwa dashboard. The jq tool is used to process JSON data in the command line. The Sensu config.json file contents specify the Redis transport and API access information as shown below:

```
{
  "transport": {
    "name": "redis"
  },
  "api": {
    "host": "127.0.0.1",
    "port": 4567
  }
}
```

The client.json file sets the environment to 'development' and the subscription name to 'linux' as shown



RHCA DevOps
Learn from the **Leader**
Learn from
Advantage Pro

**Highest number of
Red Hat DevOps
Training & Certification
provider in India**

D0407

RHCOE in Ansible Automation

D0405

RHCOE in Configuration Management

D0280

RHCOE in Platform-as-a-Service

D0270

RHCOE in

Atomic Host Container Administration

D0276

RHCOE in

Containerizing Software Applications

**Call us for an exciting
fee structure**

VECTRA
TECHNOSOFT **ADVANTAGE PRO**
OPEN SOURCE ACADEMY
or Vectra Technosoft Pvt. Ltd.
Networking with success

Red.Off: Wing 1 & 2, IV Floor,
Jhaver Plaza, 1A, N.H Road,
Nungambakkam, Chennai - 34.

Phone: 98409 82184 / 85

E-mail: enquiry@advantagepro.in

www.advantagepro.in