

and control-pulse spillover. Robust systems should include leakage reduction units, dynamical decoupling, calibrated pulse shaping, tunable couplers, isolation structures, and frequency-allocation strategies. Suppressing correlated errors is particularly important because they can bypass the protection assumptions of many quantum error correction codes and cause logical failures more rapidly.

Adopt automated calibration and drift correction: Quantum devices are highly sensitive to thermal fluctuations, magnetic-field variations, charge noise, laser instability, and control-electronics drift. Manual calibration is not scalable for large processors. Robust systems should use automated calibration routines driven by real-time diagnostics and feedback. These routines should continuously update qubit frequencies, gate amplitudes, pulse phases, readout thresholds, coupler biases, and timing parameters. Machine learning-based calibration and Bayesian optimisation are increasingly useful for maintaining stable device performance across large qubit arrays.

Develop fault-tolerant logical operations, not only protected memory: Preserving quantum information is only one part of robustness; useful computation requires fault-tolerant logical gates, measurements, and state preparation. Techniques such as lattice surgery, code deformation, transversal gates, magic-state distillation, and logical teleportation should be incorporated into the system design. These methods allow logical operations to be performed while keeping errors contained. Since magic-state distillation can dominate resource cost in universal quantum computation, architectures should optimise distillation factories, logical-routing paths, and scheduling of logical operations.

Benchmark performance at the logical level: Improvements in physical qubit fidelity are important, but the true measure of a robust quantum

system is whether the logical error rate decreases as code distance increases. Systems should therefore be evaluated using logical benchmarking, repeated syndrome-cycle experiments, memory lifetime tests, logical gate fidelity measurements, and error-suppression scaling studies. Demonstrating that larger codes produce lower logical error rates is a critical milestone towards practical fault-tolerant quantum computing.

Use hardware-aware compilation and error mitigation together with error correction: Near-term and early fault-tolerant systems should combine quantum error correction with hardware-aware software methods. Compilers should map circuits onto the most reliable qubits, reduce two-qubit gate depth, avoid high-crosstalk regions, and schedule operations to minimise idle errors. Error mitigation methods such as zero-noise extrapolation, probabilistic error cancellation, symmetry verification, and dynamical decoupling can also improve output quality, especially before fully fault-tolerant logical computation becomes available.

Plan for modularity, manufacturability, and thermal scalability: Large-scale quantum systems may require millions of physical qubits for commercially

relevant fault-tolerant applications. Therefore, robustness must include practical engineering concerns such as chip yield, cryogenic heat load, interconnect density, packaging, signal multiplexing, and modular expansion. Modular quantum computing architectures using photonic interconnects, distributed logical qubits, or networked quantum processing units can reduce the difficulty of scaling a single monolithic processor. Robust quantum systems must be designed not only to function in laboratory demonstrations but also to operate reliably in cloud-accessible, continuously maintained quantum computing environments.

Future outlooks envision quantum computers with integrated error correction, capable of tackling complex tasks across industries. Examples include quantum cloud services offering reliable computation for finance and pharmaceuticals, and quantum networks with built-in error correction for secure communication.

Building robust systems will require holistic approaches, combining error correction with fault-tolerant architectures and adaptive algorithms. Collaboration between hardware manufacturers, software developers, and end users is critical to realising the full potential of quantum computing. **END** 

References

- <https://math.mit.edu/~shor/NewDirections/lecture2.pdf>
- <https://link.springer.com/book/10.1007/978-3-031-06833-1>
- <https://thequantuminsider.com/2026/03/16/understanding-quantum-error-correction/>
- <https://www.quera.com/glossary/quantum-error-correction>
- <https://iiis.tsinghua.edu.cn/info/1044/4889.htm>
- <https://www.sciencedirect.com/science/article/pii/S0005109824004813>

By: Dr Magesh Kasthuri and Dr Anand Nayyar

Dr Magesh Kasthuri is a PhD in artificial intelligence and the genetic algorithm. He currently works as a distinguished member of the technical staff (master) and chief architect at Wipro Ltd. This article expresses his views and not of the organisation he works in.

Dr Anand Nayyar is a PhD in wireless sensor networks and swarm intelligence. He works at Duy Tan University, Vietnam, and loves to explore open source technologies, IoT, cloud computing, deep learning, and cyber security.