

```

5. """
6. # Create windows of data to compare
7. price_windows = [price[i:i+window] for i in range(len(price)-window)]
8. indicator_windows = [indicator[i:i+window] for i in range(len(indicator)-window)]
9.
10. signals = np.zeros(len(price))
11.
12. for i, (p_window, i_window) in enumerate(zip(price_windows, indicator_windows)):
13.     # Check if price is making lower lows
14.     if p_window.min() == p_window.iloc[-1] and p_window.iloc[-1] < p_window.iloc[0]:
15.         # Check if indicator is making higher lows (bullish divergence)
16.         if i_window.min() != i_window.iloc[-1] and i_window.iloc[-1] > i_window.iloc[0]:
17.             signals[i+window-1] = 1
18.
19.     # Check if price is making higher highs
20.     if p_window.max() == p_window.iloc[-1] and p_window.iloc[-1] > p_window.iloc[0]:
21.         # Check if indicator is making lower highs (bearish divergence)
22.         if i_window.max() != i_window.iloc[-1] and i_window.iloc[-1] < i_window.iloc[0]:
23.             signals[i+window-1] = -1
24.
25. return pd.Series(signals, index=price.index)
26.
27. # Detect RSI divergence
28. apple['RSI_Divergence'] = detect_divergence(apple['Close'], apple['RSI14'])
29.

```