

While developer activity is incredibly important, it is also notoriously hard to quantify with accuracy. Most cryptoasset projects are stored and orchestrated through GitHub, which has its own set of graphs of developer activity. Graphs include categories like contributors, commits, code frequency, punch card, and network, though many of them lack meaningful data. For example, while a graph can be seen on contributions, sometimes more contributions can be a negative factor if it was associated with a major bug being found in the software and developers rushing to fix it. Furthermore, each cryptoasset is composed of many different projects, which makes getting a broad view on GitHub hard to do.

As a solution, CryptoCompare has sought to amalgamate developer activity and metrics to make it easier to compare the different cryptoassets. [Figure 13.9](#) is a graph with a metric CryptoCompare has created called *Code Repository Points*,¹² which they explain as follows: “Code Repository points are awarded as follows: 1 for a star, 2 for a fork (somebody trying to create a copy or just play with the code), and 3 for each subscriber.”

A star is when someone stars code on GitHub, which users do to bookmark the code and show appreciation for it.¹³ We explained forks in detail in [Chapter 5](#) around the DAOsaster, but in this instance, a fork is a good thing. It refers to a situation where new developers forked the code of the cryptoasset to experiment with it. Recall that this is how Litecoin, Dash, and Zcash were created from Bitcoin: developers forked Bitcoin’s code, modified it, and then re-