

in Windows 7 will further accelerate the evolution of human-computer interfaces.

Though the technology to read and interpret human gestures, and physical touching, already exists, part of the challenge lies in developing a codified understanding of such actions. Researchers need to build a library of what gestures mean.

The success of the iPhone has initiated the first common standards around multi-touch: pinch, touch and sweep. And many believe that gesture-based controls will be the next mainstream evolution of human computer interfaces. Rather than having a multi-touch screen, the future devices will be controlled by air-based gestural movements of the device.

Bendable keyboard

Your couch may be comfortable, but it is not easy for you to sit back, relax and type on your wireless keyboard.



Phantom Lapboard

The keys are not at the right angle and there is no flat surface for a mouse. So John Landino has built the Phantom keyboard with a twirling, tilting mechanism for positioning it just right. This lapboard allows you to have complete keyboard and mouse interaction from just about any type of position. You can use it as a lefty or righty.

Adding wireless connections and

rechargeable batteries are just the first hurdles for moving a keyboard from the desk to people's couches, laps and beds. The Phantom Lapboard sits on your lap, but can tilt up to make typing more comfortable. If the angle is not ideal, the board will also twirl around giving you another axis to adjust. A platform on the side offers a flat, stable location for a mouse.

Landino's company Phantom



MBI6651

Hysteretic PFM Constant Current DC/DC Converter



Macroblock solution for applications in signage, decorative lighting (MR16), street lighting and automotive lighting.


High Efficiency

High Accuracy

High Dissipation

- Constant output current : 350mA~1A
- Wide input voltage range : 9~36V
- High efficiency : 93% @ input voltage 12V, 1A, 3-LEDs
- Excellent output current accuracy : ±3% (typ.); ±5% (max.)
- Hysteretic PFM improves efficiency at light loading
- Low Rds(on) : 0.45ohm
- Full protection : Thermal/UVLO/Start-Up/LED Open-/Short- Circuit
- Only 4 external components required
- Backward compatible with MBI6650 in package
- Three packages available:
 - Miniaturized solution : SOT-23
 - High power dissipation solution : MSOP-8, TO-252

PCB Actual Size



Hysteretic Pulse Frequency Modulation (PFM)

- Regulate inrush current and limit ripple current
- Adaptive output switching frequency
- Audio frequency skip : Switching frequency > 40kHz



Floor 6-4, No. 18, Pu-Ting Rd., Hsinchu 30072, Taiwan, R.O.C.
Tel: +886-3-579-0068 • Fax: +886-3-579-7534
Website: www.mblock.com.tw • Email: marketing@mblock.com.tw