

ISO 9001  
BUREAU VERITAS  
Certification



**MECO**<sup>®</sup>  
SINCE 1962

## Single Phase Multifunction Meter



MECO supports  
Bureau  
of Energy Efficiency  
(BEE), Govt. of  
India's mission to  
institutionalize  
certification of  
Electric / Electronic  
goods for  
ECOMARK under  
Gazette of India



### Features

- 10 Parameters in One Meter
- Measures V, A, PF, Hz, KW, KVA, KVAR, KWh, KVAh & KVARh
- Auto Scroll / Manual Scroll Display (User Selectable)
- Reduces Panel Space and Wiring Time
- State of The Art Microcontroller Design
- User Programmable CT Ratio (1.00 - 99.99)
- Ideal for Testing of Electrical Appliances
- TRMS Reading
- LCD Display with Backlight (20mm Digit Height)
- RS 485 Port (5kV Isolated) (Optional), please inquire sales@mecoinst.com
- MODBUS RTU Protocol (Optional), please inquire sales@mecoinst.com

### Application

- Appliance Testing
- Energy Audit
- QC
- Studying Energy Efficiency of Electrical Equipment
- Building Management Systems
- Power Management
- Generator / Motor Characteristics
- Plant Maintenance

### Specification

| Functions                           | Input Range              |                         |                         | Accuracy                                    |
|-------------------------------------|--------------------------|-------------------------|-------------------------|---------------------------------------------|
| RMS Voltage                         | 50.0 ~ 300 Vrms          |                         |                         | ± 0.2% of F.S. + 1 dgt.                     |
| RMS Current<br>(any one range only) | 1A<br>(0.05 ~ 1.2 Arms)  | 5A<br>(0.25 ~ 6.0 Arms) | 10A<br>(0.50 ~ 12 Arms) | ± 0.2% of F.S. + 1 dgt.                     |
| Active Power                        | 0.005 ~ 0.300 KW         | 0.015 ~ 1.5 KW          | 0.050 ~ 3.000 KW        | ± 0.5% of F.S. + 1 dgt. (Cosφ=0.3 to 1.000) |
| Apparent Power                      | 0.005 ~ 0.300 KVA        | 0.015 ~ 1.5 KVA         | 0.050 ~ 3.000 KVA       | ± 0.5% of F.S. + 1 dgt.                     |
| Reactive Power                      | 0.005 ~ 0.300 KVAr       | 0.015 ~ 1.5 KVAr        | 0.050 ~ 3.000 KVAr      | ± 1.0% of F.S. + 1 dgt. (Sinφ=0.3 to 1.000) |
| Power Factor                        | 0.3 Lag ~ 1.0 ~ 0.3 Lead |                         |                         | ± 0.01 PF + 1 dgt.                          |
| Line Frequency                      | 45.00 ~ 65.00 Hz         |                         |                         | ± 0.1 Hz                                    |
| Active Energy (KWh)                 | 0000 ~ 9999 KWh          |                         |                         | Class 1                                     |
| Apparent Energy (KVAh)              | 0000 ~ 9999 KVAh         |                         |                         |                                             |
| Reactive Energy (KVArh)             | 0000 ~ 9999 KVArh        |                         |                         |                                             |

## MECO INSTRUMENTS PRIVATE LTD.

Plot No. EL-1, MIDC Electronic Zone, TTC Indl. Area, Mahape, Navi Mumbai 400 710. (INDIA)  
Tel : 0091-22-27673311-16 (Sales), 27673300 (Board) • Fax : 0091-22-27673310, 27673330  
Email : sales@mecoinst.com • Web : www.mecoinst.com