

continuous display of load voltage and current/power on the front panel.

With voltage range of 2-60V DC, current range of 0-120A and power range of 600W, the EL 601 is useful for testing of switching power supplies, SMPS units, DC power plants, DC-DC converters, solar chargers, variable power supplies, telecom power supplies, medical power supplies, solar charge controllers, redundant power supplies, hot-swappable power supplies, multi-output power supplies, battery chargers, float-cum-boost chargers, DIN rail power supplies and other DC sources such as fuel cells and batteries.

Prime Electronics, Gandhinagar

Fax: (079) 23287526

Phone: 23287527

E-mail: info@prime-electronic-load.com

Web: www.prime-electronic-load.com

TEST & MEASUREMENT

Spectrum analysers

With a bright colour display to analyse any kind of signal within the frequency range of up to 1 GHz, ATL's SPA01 spectrum analyser meets the RF measurement needs of educational



setups and the industry. This low-cost, high-performance digital synthesised RF measurement instrument has a tracking generator with 16-bit half numerical display (center frequency, 0.01MHz resolvability) and intermediate frequency and 4kHz video filters.

ATL, Navi Mumbai

Phone: (022) 27682281-83

E-mail: sales@adtronindia.com

Web: www.adtronindia.com

Thermal imager

SUMITRON has introduced a low-cost, high-performance camera from Ideal Industries, USA, that blends

visible images with infrared images to track down problems that threaten the continuous operation of server rooms and data centres. The HeatSeeker detects hotspots in servers, UPS batteries and electrical connections before costly system failures occur. It also measures temperature fluctuations in cooling systems.

Sumitron Exports Pvt Ltd, New Delhi

Fax: (011) 41410494, 25891761

Phone: 41410631-35


E-mail: sumitron@vsnl.com, sumitron@airtelmail.in

Web: www.sumitron.com



Electronic weighing scale

Innovative Systems has developed an electronic weighing scale with built-in thermal printer. This machine generates bill without the need of computer and is suitable for those retailers who don't want to keep computer.



The machine is equipped with a 16-bit, low-power, high-speed Renesas microcontroller and 24-bit sigma-delta analogue-to-digital converter with an accuracy of 1 gm at 35 kg. It has two sets of 4-window, 6-x7-segment displays (one for customer and second for retailer) to show weight, rate of the item, amount and total amount of all the items purchased by the customer. A separate RS-232 port is available to connect additional booth display. Out of 100 preprogrammed items with their names and rates, 32 items can be accessed directly from the memory via a separate 4x4 keyboard.

Innovative Systems, Noida

E-mail: sales@innovativesystems.in

COMPONENTS

Quad-band GSM/GPRS data and voice modules

The wireless transceiver modules from x-blox are optimised for low-cost, mass-market, location-based applications

requiring mobile connectivity.

Featuring low power consumption and GSM/GPRS class 10 data transmission with voice capability, the LEON G100 and G200 combine base band, RF transceiver, power management unit and power amplifier in a single, easy-to-integrate solution. These are ideally suited for M2M and automotive applications such as automatic meter reading, remote monitoring automation and control, surveillance and security, e-call, road pricing, asset tracking, fleet management, anti-theft systems and point-of-sale terminals.

Omniscient Electronics Pvt Ltd, Bangalore

Phone: (080) 267144

E-mail: hemanth@omniscientelectronics.com



Low-power microcontrollers

Microchip Technology has announced a new family of 8-bit PIC microcontrollers (MCUs) featuring nanoWatt XLP technology, which enables extremely low sleep currents. The high-performance, low-power PIC18F13K22, PIC18LF13K22, PIC18F14K22 and



PIC18LF14K22 (PIC18F1XK22) MCUs are available in 20-pin packages and provide 1.8V-5.5V operation, with up to 16Kb Flash program memory.

nanoWatt XLP technology allows the PIC18F1XK22 MCUs to operate longer using less power, or with fewer battery changes, by enabling sleep current of 34 nA, typical at 1.8V; timer-1 oscillator currents of 800 nA, typical at 1.8V, 32 kHz; and watchdog timer currents of 300 nA, typical at 1.8V.

eCHIP Infotek (P) Ltd, Bangalore

Phone: (080) 25458008

E-mail: chiptech@vsnl.com