

UNMATCHED TECHNOLOGY FROM JAPAN

DIGITAL MULTIMETER - PC5000/ PC500



- 50000 count or 500000 count (PC5000 only)
- 5000 count (PC500 only)
- DCV: 1000V
- ACV: 1000V
- DCA: 10A
- ACA: 10A
- Resistance: 50M Ω
- Capacitance: 9999 μ F
- Frequency: 5Hz~200kHz
- Logic frequency: 5Hz~2MHz
- Duty cycle: 0.1%~99.99%
- dBm: -1.75dBm~54.25dBm at 600 Ω
- 4.20mA test: 0%, 20mA $\pm$ 100%
- Continuity Buzzer sounds at between 250 Ω and 2000 Ω
- Diode test: Open voltage: approx. 3.5V

DIGITAL MULTIMETER - CD772/CD771



- 4000 count
- DCV: 1000V
- ACV: 1000V
- DCA: 15A/CD772/10A/CD771
- ACA: 15A/CD772/10A/CD771
- Resistance: 40M Ω
- Capacitance: 100 μ F
- Frequency: 100kHz
- Continuity Buzzer sounds and LED lights up at between 0 Ω and 85 Ω
- Diode test: Open voltage: approx. 1.5V
- Temperature: -20 $^{\circ}$ C~300 $^{\circ}$ C (CD772 only)
- Battery check: Approx. value 1.5V (battery only (CD771 only))

DIGITAL MULTIMETER - CD800A



- 4000 count
- DCV: 600V
- ACV: 600V
- DCA: 400mA
- ACA: 400mA
- Resistance: 40M Ω
- Capacitance: 100 μ F
- Frequency: 5Hz~100kHz
- Duty Cycle: 20%~80%
- Continuity Buzzer sounds at between 10 Ω and 120 Ω
- Diode test: Open voltage: approx. 1.5V

POCKET DIGITAL MULTIMETER - PM11



- 4000 count pocket tester
- 0.8% best accuracy
- Analog bar graph
- Test lead can be snapped into a fixed position atop the case.
- Sampling rate: 1.3 times/sec
- DCV: 500V
- ACV: 500V
- Resistance: 40M Ω
- Continuity Buzzer sounds at less than 35 Ω
- Diode test: Open voltage: approx. 3V

ANALOG MULTIMETER - CX506A



- 26ch switch Capacitance measurement
- 50pF~2000 μ F
- High input impedance 50k Ω /V (DC3~300V range)
- Switchable DC polarity
- DCV: 1000V
- ACV: 750V
- DCA: 0.3A
- Resistance: 50M Ω
- Capacitance: C1: 50p~0.2 μ F C2: 0.01 μ ~20 μ F C3: 1~2000 μ F
- Transistor hFE: 1000

ANALOG MULTIMETER - YX360TRF



- Protective body cover
- Capacitance, dB, LI measurement
- Drop shock proof meter
- High resistance up to 200M Ω with low voltage
- DCV: 1000V
- ACV: 750V
- DCA: 0.25A
- Resistance: 200M Ω
- Load current: 1.5 μ A
- Capacitance: 10 μ F
- dB: -10dB~+22dB (for 10VAC)~+62dB
- hFE: 1000 at X 10 range (optional probe "hFE-6T" is necessary)

DIGITAL INSULATION RESISTANCE TESTER MG SERIES



- MG1000 1000V/500V/250V (400M Ω)
- MG500 500V/250V/125V (400M Ω)
- MG125 125V/50V/25V (40M Ω)
- ACV/DCV: 600V
- Buzzer and ALARM indicator
- Line circuit detection
- Large display with backlight
- Automatic data hold function

ANALOG INSULATION RESISTANCE TESTER DM SERIES



- DM1528S 1000V/2000M Ω 500V/1000M Ω 250V/500M Ω
- DM1008S 1000V/2000M Ω 500V/1000M Ω
- DCV: 600V
- ACV: 60V
- One-shot or continuous measurement push switch
- Auto discharge function
- Inner battery check range
- Shoulder Strap

DIGITAL CLAMP METER - DCL1200R



- Lightweight approx. 290g
- ACA: 1200V
- DCV: 600V
- ACV: 600V
- Resistance: 600 Ω
- Frequency: 30kHz
- Capacitance: 2000 μ F
- Continuity: 0 Ω and 155 Ω
- Diode test: Open voltage: approx. 1.6V