

accurate and stable pressure measurement in a 14-pin SOIC (small-outline integrated circuit) package. It is available in either 14-bit digital or amplified output. It offers less than 1.5 per cent of full-scale total error band.

GE Sensing & Inspection Technologies,
Bengaluru

Fax: (080) 41571322

Phone: 41571331

E-mail: rekha.menon@ge.com

Web: www.gesensinginspection.com

Halogen-free flame retardant label

Brady Corporation has launched the B-8088 UL 94 VTM-0 halogen-free flame retardant label. The product features self-extinguishing properties to help reduce the spread of fire in potential fire hazards found in portable or handheld devices.



B-8088 complies with International Electrotechnical Commission (IEC) 61249-2-21 specifications of halogen-free definition. In addition, it combines with Brady halogen-free thermal transfer ribbon R-6200 to give the user a complete halogen-free solution to flame retardant labeling identification.

Some of the common applications are: battery pack labels, electronic insulator labels, components identification, power cable and facilities identification.

Brady Company India Pvt Ltd, Bengaluru

Fax: (080) 41485684

Phone: 66582900, Extn. 620

Web: www.bradyyindia.co.in

Chip-on-board LED flexistrips

Binay Opto Electronics has introduced LED flexistrips which use chip-on-board (COB) technology to directly place the LED chip on a heat-sinking metal board. COB allows rapid dissipation of generated heat and keeps the LED P-N junction at a low temperature.

COB is used for both small chip and high-power chips to give long life and high reliability. In the COB production process, LED chips are directly attached to the metal PCB substrate, so that the heat generated



at the P-N junction has a direct path for maximum heat dissipation. While this process demands a high competence in engineering and manufacturing technology, it eliminates the major bottleneck of the lead-in wires for heat dissipation, as the entire chip now rests directly on the metal surface.

Additionally, non-degrading silicone encapsulant (which does not 'yellow' over time) is used to encapsulate the chip, thus prolonging the life of the product.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22102039, 22103807

E-mail: info@binayLED.com, binay@vsnl.com

Web: www.binayLED.com

Embedded USB host controller

Future Technology Devices International has launched an extended operating temperature version of its embedded USB host controller, Vinculum VNCIL-1A. The device is now



specified to operate over the temperature range of -40 to +85 degree C.

Handheld personal electronics devices such as personal media players, GPS navigation, cellular phones and digital cameras can benefit from VNCIL's embedded USB host capabilities.

VNCIL provides USB host interface and data transfer, and supports

popular device classes of mass storage, printer and human interface device (HID). HID class devices typically include keyboards and mice. When interfacing with flash drives, VNCIL manages the file allocation table (FAT) structure by using a straightforward command set. The device has 8- and 32-bit custom processor cores, dual DMA controllers, 64k embedded flash and 4k internal SRAM (static random access memory).

It features two independent USB 2.0 low/full speed, host/slave ports. These can be configured as either UART (universal asynchronous receiver/transmitter), serial peripheral interface (SPI) or parallel FIFO interfaces. It also has up to 28 general-purpose I/O (GPIO) pins available depending on configuration.

VNCIL is configured via the UART interface using a choice of free, downloadable firmware—no external software control required. It operates from a single +3.3V supply with +5V tolerant inputs. It has a low operational power requirement of 25mA and 2mA when in standby mode.

Embedded Systems Solutions, Bengaluru

Fax: (080) 23475615

Phone: 23577924

E-mail: sales@embeddedindia.com

Han EEE series

Harting Technology Group has launched the Han EEE series which features a space-saving and compact design.



The series is claimed to offer the highest contact density that

has ever been possible in a monoblock with Han E crimp contacts.

It is available in two sizes—Han 40 EEE (40 crimp contacts/size 16 B) and Han 64 EEE (64 crimp contacts/size 24 B).

Harting India, Gurgaon

Fax: (0124) 4009417

Phone: 4009415

E-mail: abhishek.bimal@HARTING.com

Web: www.harting.com