

>Syn Rec MOSFET
>40V
>60V
>75V
>100V



Lower $R_{DS(on)}$ Higher Performance

Part Number	V_{DS} (V)	I_D (A)	$R_{DS(on)}$ Max @ $V_{GS}=10V$ (m Ω)	Qg (nC)	Package
IRFS3004-7PPBF	40	240	1.25	160	D ² PAK-7
IRFP4004PBF	40	195	1.7	220	TO-247
IRFS3004PBF/ IRFB3004PBF	40	195	1.75	160	D ² PAK/ TO-220
IRFR4104PBF	40	30	5.5	59	D-PAK
IRFS3006-7PPBF	60	240	2.1	200	D ² PAK-7
IRFS3006PBF/ IRFB3006PBF	60	195	2.5	200	D ² PAK/ TO-220
IRFB3206PBF	60	210	3.0	120	TO-220
IRFS3206PBF/ IRFP3206PBF	60	210	3.0	120	D ² PAK/ TO-247
IRFR1018EPBF	60	79	8.4	69	D-PAK
IRFP4368PBF	75	195	1.85	380	TO-247
IRFS3107-7PPBF	75	240	2.6	160	D ² PAK-7
IRFS3107PBF	75	195	3.0	160	D ² PAK
IRFB3077PBF	75	210	3.3	160	TO-220
IRFR3607PBF	75	80	9.0	84	D-PAK
IRFP4468PBF	100	195	2.6	360	TO-247
IRFS4010-7PPBF	100	190	4.0	150	D ² PAK-7
IRFB4110PBF	100	120	4.5	150	TO-220
IRFS4010PBF	100	180	4.7	143	TO-220
IRFP4568PBF	150	171	5.9	151	TO-247
IRFB4115PBF	150	104	11.0	77	TO-220
IRFS4115PBF	150	99	12.1	77	D ² PAK

- Tailored for Synchronous Rectification
- Optimized for fast switching
- Up to 20% lower $R_{DS(on)}$ *
- Up to 20% increase in power density*
- RoHS Compliant
- Lead Free

*Compared to previous generations

**Your FIRST CHOICE
for Performance**

For more information, please visit us at www.irf.com or www.irf.com.cn.

International
IR Rectifier
THE POWER MANAGEMENT LEADER