



THE MASTERMIND WITHIN

A ONE STOP CONTRACT MANUFACTURING with SMT SETUP

GSM/GPRS MODEM



A ready-to-use Tri Band GSM/GPRS modem for voice data, fax and SMS services.

- Easily controlled by using AT commands.
- RS 232 port and telephone like audio plug.
- Built in TCP/IP stack.

• Application in Security Management System • Intelligent House/Vehicle Security and Tracking System • Automation • Wireless Data Transfer System • Remote Monitor And Control System

ELECTRONIC MANUFACTURING SERVICES

Pulraj is a state-of-the-art provider of EMS for PCB assemblies, catering to consumer, industrial, automotive, medical, telecom, computer and data storage, defence needs and more.

Facilities

• A fully automated SMT line for SMDs, Connectors, Sockets, BGAs and QFPs. • Lead-free process.

Services

- Cost-effective manufacturing solutions. • In-house R&D set-up.
- Product design and development. • Prototyping to volume production. • On-going cost reduction focus. • Global component sourcing. • Effective inventory control.
- Complete customer satisfaction.

PULRAJ

Electronics Pvt. Ltd.

Works : D 28/14, Behind Turbhe Tel. Exchange, TTC, MIDC, Navi Mumbai. Tel : 022-2768 5069
www.pulraj.com Email : info@pulraj.com

AN ISO 9001:2000 company



- EX-STOCK in rupees
- GPS-Engine boards
- GPS-Data logger
- GPS-GSM development boards

23 Modules for different applications



SR-92



SR-88



SR-101



MR-99



MR-87

24hrs Samples Delivery

Contact: Ms. Saritha Business Development Manager

NGE Services & Consultancy

#104, Kochar Apartment, Begumpet, Hyderabad-500 016.

Tel:040 - 27760647/27765647

e-mail: gps@ngesc.com

MAGIC SINE : TRANSFORMER-LESS FERRITE PURE SINE WAVE INVERTER 600VA

THIS IS BASED ON SMR TOPOLOGY IN TRANSFORMER-LESS HIGH FREQUENCY FERRITE BASED PURE SINE WAVE INVERTER.

REVERSIBLE INVERTER - VERY LOW COMPONENT COUNT AND VERY LOW MATERIAL COST !!!

MEDI's reversible inverter is different from conventional method of high frequency inverter which converts the battery voltage to high voltage DC using diodes. This high voltage DC is then converted to 230V AC. So, if we are giving battery voltage we will get AC output, but if AC input is given back to the AC output, it will not charge the battery, that means you will not get DC output at the battery terminal because high voltage diode will block the reverse flow. But, in the conventional transformer type inverter, it is a natural reversible inverter. If you give AC input back to the AC output, it will charge the battery. This is how our inverter works though it is transformer-less!

There are two very big advantages which will increase reliability in our SMR reversible inverter -

1. In case of inductive loads, the current will flow reverse in some portion of the wave due to lagging p.f. This power has to go to the battery and charge it. This will not happen in conventional high frequency inverters instead this power may damage the output switching device like mosfet or IGBT. This is the main reason for the high failure rate of high frequency designs in the market. Because our inverter is reversible, this power will charge the battery. So, the output stage will be safe. Hence the reliability is high.
2. Since our inverter is a reversible inverter, the same inverter is used for charging. There is no need for an extra charger. Normally in conventional high frequency inverters, for avoiding the additional charger, you have to use more number of relays for disconnecting the bridge from the output stage and use the same bridge for charging. In this indirect method the failure chances are more.

Features: > High efficiency transformer-less ferrite core based design > More battery back up compared to conventional inverters > Battery input, AC input and AC output will come directly from the single PCB > Active Power Factor Corrected SMPS charger so very less current consumption from mains while charging > No current consumption from mains while charger is cut > Pure sine wave output, harmonic distortion less than 2% > Very few components, single sided PCB, no smd components > Very low manufacturing cost and light weight, less heat dissipation > Fold back current limiting protection for short circuit and overload > High voltage, low voltage protection > All the set-up through LCD > Complete set up and monitoring through RS-232 > LED board can be cut and removed from the main board



No product, only technology

Technology cost - Rs.2,50,000. Bill of material of 600VA = Rs.1600

Medi www.magicsineferrite.com

Martin's Electronic Devices & Instruments

Cochin Office: 39/2067, Manikiri Cross Road, Cochin 682016. Email: cochin@medielectronics.net

Ph/fax: 0484-3018 601-605, 2312527(R), 093886 15176(R-Mob)

Bangalore Off: 23, 4th cross, Hutchins Road, B'lore, 560 084 Ph : 080-32507441, Mob:09886608340

Delhi - 09212387080 Email : bangalore@medielectronics.net Web: www.medielectronics.net