

IEC 61850-3 Compliant Ethernet Switches

Maximize Availability of Substation Communication Networks

The PowerTrans series of Ethernet switches features the highest level of reliability and availability of substation communications, offering superior EMI/RFI shielding, -40 to 85°C operating range, and redundant media and power for challenging substation environments. Maximum exibility is achieved by a ruggedized and modular rackmount design with high optic ber and gigabit port density suitable for retrofit and new substation networks. PT-7828 supports Layer 3 routing for better network performance.

IEC 61850-3
Up to 22 Fiber Ports
-40°C to +85°C
Layer 3 Routing

- Layer 3 routing splits a large-scale LAN into multiple subnets (PT-7828)
- IEC 61850-3 and IEEE 1613 compliant in a rack
- Meets NEMA TS2, EN50155, EN 50121-4 standards
- Faster network fault recovery (under 20 milliseconds)
- Integrated dual redundant power supplies of 24/48 VDC, or 110/220 VDC/VAC
- Fan-less cooling design, -40 to 85°C operating range

IEC 61850-3 Compliant Ethernet Switches



PT-7828 Layer 3 24+4G-port Managed Ethernet Switch



PT-7728 Layer 2 24+4G-port Managed Ethernet Switch



PT-7710 8+2G-port Managed Ethernet Switch



PT-7324 22+2G-port Smart Ethernet Switch



http://www.moxa.com/support/White_Papers.htm

MOXA®



DYNALOG
(INDIA) LIMITED

Kailash Vaibhav, G Wing,
Vikhroli Parksite, Vikhroli (West)
Mumbai - 400 079, INDIA

Tel: 91-22-2518 1900 (16 Lines)
Fax: 91-22-2518 1930/1940
www.dynalogindia.com
sales@dynalogindia.com