

New Products

LIGHTING

LED Lighting

Seoul Semiconductor has launched a high-efficiency, SMD-type LED for general-purpose lighting. Unlike existing chip LED devices, the LCW100Z1 delivers over 120 lm/W with an enhanced primary optic. Combined



with the metal substrate, luminous efficiency is improved substantially compared to the typical top-view LED. Enhanced heat transfer dramatically improves efficiency.

As an ultra-thin LED with dimensions of $3.5 \times 2.8 \times 1.6 \text{ mm}^3$, the LCW100Z1 delivers up to 7.8 lm (@0.06W) at a low current of 20 mA, and 14.3 lm at 40 mA with a viewing angle of 120 degrees in cool white.

Seoul Semiconductor, New Delhi

Phone: (011) 29893765

E-mail: gopal.shukla@led.com

49-LED flood light/search light

The Binay 49-LED white flood light/search light lasts up to 100,000 hours consuming only around 65 watts. It is shock-resistant and vibration-proof, due to its solid-state LED construc-



tion, and can withstand large variation in input voltage without change in light output.

The light can be used for powerful flood lighting applications (with wide-beam lenses), as a high-power uplighter for highlighting the exterior of building facades (from the bottom of the building upwards) and as a powerful spot light/search light (with focused-beam lenses).

Binay Opto Electronics Private Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807, 22102039

E-mail: binay@vsnl.com, info@binayLED.com

TEST & MEASUREMENT

Power-quality clamp meter

With a bright colour display to analyse the harmonic spectrum, a low-



pass filter to remove high-frequency noise, and a high EMC-immunity design, the Fluke 345 is ideal for measurements on such switching loads as variable-frequency drives, electronic lighting and UPS. The Hall Effect measurement system makes measurement of DC current possible without the need to break

the circuit, and the internal memory enables long-term logging for analysis of trends or intermittent problems.

TTL Technologies Pvt Ltd, Bangalore

Fax: (080) 25291285

Phone: 25260646, 25251859

E-mail: ig@tthindia.com

Web: tthindia.com

Glossmeter

Mangal Instrumentation has introduced a compact, sensitive glossmeter in two models: mains operated for

laboratory purpose and battery operated with measurement geometries of 45 degrees, 60 degrees, 85 degrees, etc. It can be used for the measurement of gloss/brightness of paints, tiles, sanitary products, coatings, moulded



surfaces, plastic doors, glass, ceramic products, opaque glasses, porcelains, paper, cloth, pigments, flours, powder, etc. It is also useful for measuring the brightness/whiteness of plantation white sugar and reflectance of fabrics.

Mangal Instrumentation, New Delhi

Fax: (011) 29841033


Phone: 65845192

E-mail: mangal_india@vsnl.com

Web: mangalinstrumentation.com

Photoelectric sensor

Shiva Electronics has developed a photoelectric diffuse-beam sensor with 1200mm sensing range (adjustable) and built-in on-off delay of 0-30 seconds.



The sensor operates off 90V-260V AC / DC supply and provides potential-free relay

output contacts. It comes with a five-core cable, of which two cores are for supply and three cores for N/C-C-N/O relay contacts.

The sensor finds wide applications in textile, plywood, packaging, paper and cement industries.

Shiva Electronics, Nashik

Fax: (0253) 2511565

Phone: 6566565

E-mail: info@shiva-electronics.com