

of measurement tools including the world's fastest, most capable oscilloscopes, logic analysers for real-time digital systems analysis, the world's first real-time spectrum analysers capable of visualising a live RF spectrum revealing signal anomalies, the fastest arbitrary signal sources to test design margins, mixed-signal oscilloscopes useful for embedded designs, the most complete set of video solutions (from content production to automated content quality control, and monitoring of video transmissions to ensure the best possible viewing experience), and network diagnostic and management solutions that cover fixed, mobile, IP and converged multi-service networks.

As the bandwidths used are increasing, the T&M instruments should be capable of handling high-bandwidth applications. Most of the customers in the telecom sector work on multiple technologies at a time, so the T&M instruments have to provide the facility to upgrade and install new options easily. These also need to be equipped with a selection of interfaces like GPIB LAN and USB to facilitate connection with other instruments; e.g., for remote control.

Wireless/telecom solutions need software-defined-radio (SDR) architecture with typical signal bandwidth of 40 MHz and modular instruments supporting multiple input/multiple output (MIMO) configurations, hence putting different RF sources and analysers tightly synchronised together. Of course, all this needs to be supported with a powerful GUI and user software.

Keithley offers vector signal analysers 2800-series and vector signal generators 2900-series with signal bandwidth of 40 MHz (80 MHz), ranging up to 6 GHz. Both instruments are configurable in MIMO systems up to 8-by-8 (eight analysers and eight generators). A powerful software package for signal generation, analysis and simulation complements the offering.




Agilent U1253A true-RMS OLED multimeter

For semiconductors, the major challenges are integrated pulsing, while eliminating self-heating effects, a wide dynamic measurement range from femto-amperes to 10's of amperes and similar dynamic measurement ranges for voltages.

Keithley has developed Source Meter 2600A Series, which supports pulsing with range of different ampere and volt ratings. Or, the 4200-SCS semiconductor characterisation system, which supports pulsing, with integrated scope and capacitance-voltage measurement function. All instruments can be integrated under a powerful GUI called 'advanced characterisation suit.'

Good Will Instrument has announced powerful and affordable GDS-1000A series DSOs featuring 1GSa/s sampling and 2M point memory. The family of three includes the members of 60MHz, 100MHz and 150MHz bandwidth, respectively.



Caught in a balancing act between accuracy and price?

DMMs with the perfect balance of high precision and affordable cost.



MODEL 2100 6½-DIGIT USB DMM

- **High performance family of digital multimeters** offers a wide range of price and performance options for virtually any application.
- Resolutions from 6½ to 8½ digits and built-in measurement tools to **simplify and improve even the most critical measurements.**
- High speed, low noise 28-bit A/D converter technology for **superior measurement precision, sensitivity, and traceability.**
- **Integrated switch mainframe options** simplify configuring complete test systems economically.

Go to
www.keithley.com/balance
and try a demo.

KEITHLEY

www.keithley.com
support_india@keithley.com
91-80-2677-1071, -1072, -1073