



MBI6651 Hysteretic PFM Constant Current DC/DC Converter



Macroblock solution for applications in signage, decorative lighting (MR16), street lighting and automotive lighting.

High Efficiency

High Accuracy


High Dissipation

- Constant output current : 350mA-1A
- Wide Input voltage range : 9-36V
- High efficiency : 93% @ input voltage 12V, 1A, 3-LEDs
- Excellent output current accuracy : $\pm 3\%$ (typ.); $\pm 5\%$ (max.)
- Hysteretic PFM improves efficiency at light loading
- Low Rds(on) : 0.45ohm
- Full protection : Thermal/UVLO/Start-Up/LED Open-/Short- Circuit
- Only 4 external components required
- Backward compatible with MBI6650 in package
- Three packages available:
 - Miniaturized solution : SOT-23
 - High power dissipation solution : MSOP-8, TO-252

PCB Actual Size



TO-252



Hysteretic Pulse Frequency Modulation (PFM)

- Regulate inrush current and limit ripple current
- Adaptive output switching frequency
- Audio frequency skip : Switching frequency > 40KHz



Macroblock

Floor 6-4, No. 18, Pu-Ting Rd., Hsinchu 30072, Taiwan, R.O.C.
Tel: +886-3-579-0068 • Fax: +886-3-579-7534
Website: www.mblock.com.tw • Email: marketing@mblock.com.tw

Telephone Call Recording System

For Call Centers, Banks, Hospitals, Stock Brokers,
Educational Institutions, Legal Offices...



Get in-depth call information from the secure feature-rich browser interface that incorporates an in-built audio player (with AGC) to play and analyse telephone records. The multi-featured product ensures quality customer service that will help you to maintain a strong client base globally.



Features

- Remote secure access with multi-login facility
- Compatible to work with any EPABX/CO-line
- Phone book for multiple entries
- Group calls to user-defined categories
- GSM/G.711 a-law/μ-law/PCM/MP3... formats
- Advanced search options for quick retrieval of records
- LX and DX with 1/2/4/8/12/16/.../128 ports and more
- Supports digital (ISDN PRI, R2MF, digital PBX extn.), VoIP



Xtend Technologies (P) Ltd.,
Blue Hill, Kalathiparambil Cross Road, Ernakulam South, Kochi-682016,
Kerala, India. Phone: +91-484-2378008 / 3291008, +91-9388686080,
E-mail: sales@xtendtech.com, Web: www.xtendtech.com

Dealership enquiries solicited:

Delhi 9312096080 / Kolkata 9331296080 / Bangalore 9342596080
Mumbai 9324996080 / Hyderabad 9393096080 / Chennai 9341296080

Other Products: Interactive Voice Response System (IVRS), Outbound Dialer (OBD)