

```

% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
% varargin command line arguments to
data_port_controller (see VARARGIN)

handles.i
handles.data=0;
% Choose default command line output for
data_port_controller
handles.output = hObject;

% Update handles structure
guidata(hObject, handles);

% UNWAIT makes data_port_controller wait
for user response (see UIRESUME)
% uwait(handles.figure);

% --- Outputs from this function are returned
to the command line.
function varargout = data_port_controller_
OutputFcn(hObject, eventdata, handles)
% varargin cell array for returning output
args (see VARargout);
% hObject handle to figure
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Get default command line output from handles
structure
varargout{1} = handles.output;

parport
%putvalue(data,0) initializes to zero at
every pin , XP normally has a value 255 at
data port

% --- Executes on button press in pushbutton1.
function pushbutton1_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton1 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

about_me

% --- Executes on button press in pushbutton2.
function pushbutton2_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton2 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
close

% --- Executes on button press in checkbox1.
function checkbox1_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox1 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox1
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox2.
function checkbox2_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox2 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox2
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox3.
function checkbox3_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox3 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox3
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox4.
function checkbox4_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox4 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox4
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox5.
function checkbox5_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox5 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox5
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox6.
function checkbox6_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox6 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox6
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox7.
function checkbox7_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox7 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox7
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in checkbox8.
function checkbox8_Callback(hObject,
eventdata, handles)
% hObject handle to checkbox8 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)

% Hint: get(hObject,'Value') returns toggle
state of checkbox8
handles.output = hObject;
handles.i=i+1-handles.i;
data
parport
guidata(hObject, handles);

% --- Executes on button press in pushbutton3.
function pushbutton3_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton3 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
stepper_controller
close data_port_controller

% --- Executes on button press in pushbutton4.
function pushbutton4_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton4 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
open('usermanual.pdf')

% --- Executes on button press in pushbutton5.
function pushbutton5_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton5 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
handles.i=i+1;
handles.i2=i;
handles.i3=i;
handles.i4=i;
handles.i5=i;
handles.i6=i;
handles.i7=i;
handles.i8=i;
data
parport
set(handles.checkbox1, 'value',handles.
i);
set(handles.checkbox2, 'value',handles.
i2);
set(handles.checkbox3, 'value',handles.
i3);
set(handles.checkbox4, 'value',handles.
i4);
set(handles.checkbox5, 'value',handles.
i5);
set(handles.checkbox6, 'value',handles.
i6);
set(handles.checkbox7, 'value',handles.
i7);
set(handles.checkbox8, 'value',handles.
i8);
guidata(hObject, handles);

% --- Executes on button press in pushbutton6.
function pushbutton6_Callback(hObject,
eventdata, handles)
% hObject handle to pushbutton6 (see
 GCBO)
% eventdata reserved - to be defined in a
future version of MATLAB
% handles structure with handles and
user data (see GUIDATA)
handles.i
data
parport
set(handles.checkbox1, 'value',handles.
i);
set(handles.checkbox2, 'value',handles.
i2);
set(handles.checkbox3, 'value',handles.
i3);
set(handles.checkbox4, 'value',handles.
i4);
set(handles.checkbox5, 'value',handles.
i5);
set(handles.checkbox6, 'value',handles.
i6);
set(handles.checkbox7, 'value',handles.
i7);
set(handles.checkbox8, 'value',handles.
i8);
guidata(hObject, handles);

```