

New Products

POWER SUPPLY

UPS system for data centres

APC by Schneider Electric has launched the APC Symmetra PX 250/500kW three-phase UPS system for data centres. Offering ultra-high efficiency, nearly silent operation and



N+1 redundancy, the APC Symmetra PX 250/500kW is claimed to be the world's first modular UPS system that scales in 25kW and increments up to 500kW.

This ultra-high efficient, double conversion online inverter power module extends battery life considerably. It has a large touchscreen graphical user interface and a side-mounted maintenance bypass panel with subfeed distribution. It also offers maximum data centre configuration flexibility. In the future, Symmetra PX 250/500kW would be capable of being paralleled up to 2 MW.

The UPS system is an ideal platform for business-critical applications running in large data centres.

American Power Conversion by Schneider Electric, Bengaluru

Phone: (080) 39872000

E-mail: Elizabeth.jacob@apcc.com

Web: www.apc.com

TEST & MEASUREMENT

Mixed signal oscilloscope

Tektronix has announced the MSO70000 series of mixed signal oscilloscopes. The instruments have up to 20 channels of measurement capture

(four analogue and 16 digital) with analogue bandwidth ranging from 4 to 20 GHz and 80ps digital channel timing resolution.

The MSO70000 series combines the signal visibility and timing features of a high-performance logic analyser with analogue precision, probing and usability of a high-performance real-time oscilloscope. This makes it the ideal debug and



verification tool for such demanding high-speed design applications as double data rate (DDR) memory, high-performance application-specific integrated circuit (ASIC) analogue, field-programmable gate array (FPGAs), system-on-a-chip devices and digital RF.

Tektronix (India) Ltd, Bengaluru

Fax: (080) 22275588

Phone: 22275577

E-mail: india.mktg@tek.com

Web: www.tektronix.com

Ultrasonic distance sensor

Rhydo Technologies has launched 'ECHO,' a portable and easy-to-use handy ultrasonic distance sensor that provides very short to long-range detection and ranging. The sensor provides stable and non-contact distance measurements from 2cm to 4 meters with high accuracy.

The board has high quality PCB, needs 5V DC supply voltage and the modulation is at 40 kHz. The board comes in two versions—one with serial transmission of distance (ASCII format) and the other with pulse width modulation (PWM) output. The board can easily be interfaced to microcontrollers one I/O or Rx pin. The serial data can also be received in a PC using a simple RS-232 to transistor-transistor

logic (TTL) converter.

This sensor is suitable for any application that requires measurements between moving or stationary objects. The product is very useful in robotics applications but can also be used in security systems or as an infrared replacement.

Rhydo Technologies Pvt Ltd, Cochin

Fax: (0484) 2370579

Phone: (0484) 2370444, 2371666

E-mail: sales@rhydolabz.com

Web: www.rhydolabz.com

COMPONENTS

Medium-G accelerometers

STMicroelectronics has introduced a three-axis sensor with digital output that can detect accelerations up to 24g or about 5x—the force created by a car under heavy braking. The LIS331HH's combination of multiple full-scale ranges above 10g with small pix size, high resolution and low power consumption. Its smart embedded features enable high-precision motion sensing in a wide range of consumer and industrial applications.



The MEMS accelerometer provides extremely accurate output across full-scale ranges of $\pm 6/\pm 12/\pm 24g$. The medium-g sensing enables high-level vibration monitoring and high-shock detection without any loss of information. In gaming applications, medium-g detection enhances user interfaces.

The medium-g accelerometer has high stability over a wide temperature range for both zero-g offset and sensitivity. Its ultra-compact robust design provides very high shock survivability up to 10,000g.

STMicroelectronics Marketing Pvt Ltd, Noida, Uttar Pradesh