

ance at densities of up to four million equivalent system gates and 840 user inputs/outputs for space-based applications.

Actel Pan Asia Corporation, Bengaluru

Fax: (080) 25213737

Phone: 41134794, 41515078

E-mail: Parag.kulkarni@actel.com

Web: www.actel.com

Battery-monitoring IC

STMicroelectronics has introduced a battery-condition monitoring IC enabling increased accuracy for 'fuel-gauge' style indicators showing the operating time remaining. The device



will improve the user experience for owners of such products as mobile handsets, portable navigation devices, digital cameras and personal media players.

The ST3C100 can be located in the battery pack or in the handheld device, and integrates functions to monitor the battery voltage, current and temperature. It has a built-in Coulomb counter to calculate battery charge, and stores the data at 16-bit resolution for retrieval by the system controller.

STMicroelectronics Marketing Pvt Ltd, Noida, Uttar Pradesh

Fax: (0120) 4243417

Phone: 4243400

Programmable LED blinker

Designers of mobile handsets, ultra-portable devices, consumer products and industrial/embedded systems can now implement a blinking LED solution that can easily be programmed to create an enhanced visual experience. Fairchild's programmable LED blinker—the FAN5646—eliminates the need for a microprocessor to be in continuous operation mode. With

single-wire digital interface, it can be programmed with a unique LED blink rate and pattern. When the FAN5646 is enabled, it will continually play these LED blink patterns until commanded by the microprocessor to stop.

The FAN5646 minimises system power consumption as the internal programmable LED blink pattern allows the microprocessor to remain in

sleep mode while FAN5646 is operating. Very low drop-out voltage of 80 mV enables the LED to be powered without the need for inductors or switching capacitors, minimising component count.

Fairchild Semiconductor (India) Pvt Ltd, Bengaluru

Fax: (080) 41643111

Phone: 41643113



COMPUTING

2133MHz memory for Intel Core i5 platform

Kingston Technology has started shipping memory support for Intel's new LGA1156 Core i5 and Core i7 systems. The super-fast 2133MHz HyperX memory runs at a low voltage of 1.65 volts. This XMP-ready, dual-channel, 4GB CL8 kit is a good choice for ultra-enthusiasts who are ready to take the Intel Core i5 platform to the next level of memory overclocking performance.

Kingston Technology, Inc. India Head Office, Mumbai

Fax: (022) 26592963

Phone: 26592961

E-mail: sales_india@kingston.com,

marketing_india@kingston.com

Motherboards

GIGABYTE Technology has launched P55 series Motherboards based on Intel's P55 chipset. The motherboards feature Ultra Durable 3 design with copper PCB and deliver a host of cut-

ting-edge features including 24-phase VRM design, innovative PC management tools and dynamic energy saver just to name a few.

Supporting the latest Intel Core i7 and Core i5 processors featuring LGA 1156 socket (codenamed Lynfield), the motherboards promise



high-performance computing. With the memory controller integrated directly into the processor die, these support two-channel DDR3 memory for fast memory performance of 2200 MHz and above.

GIGABYTE Technology (India) Limited, Mumbai

Fax: (022) 40633223

Phone: 40633222

Web: gigabyte.in

MISCELLANEOUS

Patch panel

DIGILINK has introduced a high-density patch panel to help you meet the demands of the ever-growing data traffic. It has a unique die-cast



aluminium design that not only saves rack space and fits in a standard 48.3cm (19-inch) rack or cabinet giving you 24 ports in a 1U panel but also provides excellent shielding to connectors. It delivers uninterrupted data at high speeds when installed in a 'total availability network.'

The patch panel is available in unloaded kit form suitable for the entire range of DIGILINK UTP Keystones. It is priced at Rs 2400 to Rs 6100.

DIGILINK, Mumbai

Phone: (022) 30616666

E-mail: sales@digilink.in