

New Products

TEST & MEASUREMENT

Video inspection system

iVue from SharpVue, a division of USA-based Avnet Inc., is a portable, easy-to-use video inspection system that can instantly capture images and provide the facility of on-screen measurement and annotation.

The system comes with an LED lighting system and a 3-megapixel built-in camera. It can capture images directly from the screen to the USB stick of the internal hard drive. The images captured can be e-mailed directly. An on-screen grid is available for measurement. There is no need for a laptop, camera, light source, stand or software to use this device.

Sumitron Exports Pvt Ltd, New Delhi
 Fax: (011) 41410494, 25891761
 Phone: 41410631-35
 E-mail: sumitron@vsnl.com,
 sumitron@airtelmail.in
 Web: www.sumitron.com

Low-resistance current sensor

Yageo Corporation, Taiwan, has launched an ultra-low-resistance current sensor for miniature portable device applications. The PF1206 features a comprehensive resistance range of 1 to 50 milli-ohms and temperature coefficient of 75 ppm/°C. Manufactured using in-house metal foil and metal alloy processing technologies to combine PCB substrate and resistance foil, it is capable of delivering 5-10 per cent less temperature rise than similar products.

Available in 0.25W and 0.5W, the PF1206 is particularly suitable for use in the power control circuit of netbooks

and notebooks, or the hard disk of other compact portable devices that have stringent space as well as current-sensing and over-current protection requirements.

Yageo Corporation, Taipei, Taiwan
 Phone: (+886) (2) 29177555; Ext: 3390
 E-mail: bryan.jhsu@Yageo.com

Sugarcube-size photoelectric switch

Shiva Electronics has developed a compact (3×2×1.3cm³), retro-reflective photoelectric switch. The sensor comes with an integrated transmitter and receiver but uses the reflector as the target. Whenever the object comes in



between the sensor and the reflector, it triggers an output signal.

This microcontrol-

ler-based sensor is available in ABS plastic and has adjustable sensing range of 50 cm. It can detect high-speed objects reliably. The reflector is available in 5.1×5.1 cm² size. The outputs have a driving capacity of 500 mA and are protected for short-circuit, over-load and inductive load. Supply voltage is 10-30V DC.

Shiva Electronics, Nagik
 Fax: (0253) 2511565
 Phone: 6566565
 E-mail: info@shiva-electronics.com

Inductive proximity sensors

R.S. Electronics has developed inductive proximity sensors that can detect the presence of a wide range of metallic targets.

The inductive proximity switch comprises a high-frequency oscillator circuit followed by a level detector and a post-amplification signal circuit, and drives a buffered solidstate out-



put. In effect, when a metallic object is brought within the effective range of the emission field of the oscillator, the amplitude shift is converted into a digital signal by the level detector, which drives a buffer stage.

The sensors are available in DC as well as AC, and in various sizes from M8 to M80.

R.S. Electronics, Chennai
 Phone: 09444659962
 E-mail: rselectronics75@gmail.com

Infrared temperature meter

Metravi has launched a non-contact forehead temperature measuring device that can measure body temperature without touching the patient.

The infrared meter provides many features like selectable body and surface temperature, selectable °C/°F scale, alarm-value settings, storage of the last 32 measurements, automatic data hold, auto power-off, temperature measurement in 0.5 second, automatic selection range and display resolution, and backlit LCD display.

The device can measure from a distance of 5-15 cm, with an accuracy of ±0.3°C (0.54°F). In body mode it can measure temperatures ranging from 32.0°C to 42.5°C (90°F to 108°F), and in surface temperature mode the range is 0-60°C (32-140°F).

Arun Enterprises, Kolkata
 Fax: (033) 22154821
 Phone: 22151376, 22159759
 E-mail: info@metravi.com
 Web: www.metravi.com

