



The Super Stick Mini Black is not only smaller in size and greater in capacity but also waterproof, dust-resistant and high-/low-temperature-tolerant (above 100°C/-40°C) without any compromise on quality and data transfer rate.

KINGSTAR Communications P Ltd,
Ahmedabad
Phone: (079) 30026883

CompactFlash cards

Transcend Information has released the Extreme Plus 600X CompactFlash (CF) cards with Turbo MLC technology. The new CF cards raise the bar with high transfer speeds of up to 92MB/s read and 87MB/s write, making them ideal for professional photographers and enthusiasts who use digital single-lens reflex (DSLR) cameras.



The cards can instantly store extremely high-resolution image data, which makes consecutive shooting and non-stop video recording easier.

Supertron Electronics Limited, Kolkata
Phone: (033) 22131221-23
E-mail: coordinator@supertronindia.com

POWER SUPPLY

Power supply-cum-LED driver

Elektronika Sales has launched 3W-150W power supply-cum-LED driver devices with power factor correction (PFC). These devices have integrated PFC and LLC controllers. Frequency- and phase-locked PFC and LLC allow for ripple cancellation in bulk capacitors for reduced ripple current, reduced bulk capacitor size and reduced EMI filter cost.



The devices can be used in LED street lights, LED interior/exterior lights, LED battery chargers

for lanterns and LED solar lanterns.

Elektronika Sales Pvt Ltd, Chennai
Phone: (044) 28587165, 28587765
E-mail: info@elektronikasales.com
Web: www.elektronikasales.com

COMPONENTS

Zero-insertion-force connector

ITT Interconnect Solutions, USA, has developed a miniature, high-reliability, zero-insertion-force connector for portable medical equipment. The QLC connector features a 260-position



pin count and is constructed with a lightweight aluminium shell. Its high pin count, miniature size and superior reliability provide customers with the ideal solution for portable ultrasound machines and other portable imaging equipment.

The connector features a quick-disconnect latch, providing easy mating and unmating, as well as EMI and RFI shielding. It can withstand up to 20,000 mating cycles.

ITT Interconnect Solutions, Santa Ana, California, USA
Fax: (001) (714) 6282249
Phone: 6288370
E-mail: nas.echeverria@itt.com
Web: www.ittdamm.com

DC-DC converter

Texas Instruments (TI) has added the TPS54620 to its easy-to-use swift power management IC family. The TPS54620 is claimed to be the smallest single-chip, synchronous, step-down DC-DC converter supporting up to 17V, resulting in a complete 6A power solution.



This 95 per cent power-efficient switcher is 60 per cent smaller than multichip converters and made

of integrated MOSFETs in a small 3x3mm² QFN package.

The 1.6MHz monolithic converter is targeted at designs in high-performance point-of-load regulation, high-density distributed power systems, broadband, networking and optical communications.

Texas Instruments (India) Pvt Ltd, Bengaluru
Fax: (080) 25048286
Phone: 25099221
Web: www.ti.com

MISCELLANEOUS

ARM7 evaluation board

NGX Technologies has launched a low-cost, feature-rich ARM7 evaluation/educational board. Called 'BlueBoard-lpc2148', the board is based on the LPC214X series of ARM7 microcontrollers from NXP Semiconductors.

BlueBoard is an open source initiative aimed at realising cost-effective prototyping and solutions. Driven by engineering and support from NGX Technologies, the board is provided with necessary interfaces for quick realisation of embedded solutions.



Developed to evaluate the LPC214X series of processors, it acts as a good platform to create and test embedded applications.

The board features RS-232 (2X), VGA, PS2, SD/MMC, USB with link LED, 256kB I²C-based EEPROM, audio power amplifier, audio jack, 2-line×16-character LCD with backlight control, configurability for manual and automatic program download (ISP) via serial port, etc. It is priced at Rs 2000.

NGX Technologies Pvt Ltd, Bengaluru
Fax: (080) 23103206
Phone: 23103205
E-mail: sales@ngxtechnologies.com
Web: http://shop.ngxtechnologies.com