

EFY Note

The source code of this project is included in this month's EFY DVD and is also available for free download on source.efymag.com website.

all the resistors in a few seconds. But always take care to choose the colour band in a sequence only, as given on the body of the resistors whose value you want to find. Otherwise, it will show a wrong value.

Standalone MATLAB application of resistor value calculator

Before using the MATLAB compiler for the first time, you must run the mbuild setup command to configure your C/C++ compiler to work with the MATLAB compiler. (The MATLAB compiler requires a supported ANSI C or C++ compiler installed on your system). This set-up step is only to be performed once.

To set up mbuid, type the following in the Command Window:

```
>>mbuild -setup
```

It will ask whether you want to locate the installed compiler. Press 'y' and then 'I' for choosing the compiler as shown in Fig. 4. Press 'y' again and your mbuid setup is installed.

If mbuid setup is not installed, an error message will appear as shown in Fig. 5.

When the installation of mbuid is completed, write following command on Command Window:

```
>>deploytool
```

Deployment Project window will open as shown in Fig. 6. Enter the name of your project, give it a path where you want to save it (we saved the project on the desktop) and chose Window standalone application option followed by pressing the 'OK' button.

The deployment tool will open as shown in Fig. 7. Now you need to add the resistor executable file under the Main File and other supporting files under the Shared Resources and Helpers Files window. Next, click on Build icon on the right side and you




Fig. 10: Command Window




Fig. 11: MCR installation




Fig. 12: MCR installation in progress

will see your project building process as shown in Fig. 7.

When building is completed, click on Package tab as shown in Fig. 8.

You will see readme.txt and .exe files. Click on Add MCR option and the MCRInstaller.exe gets added to your package.

Click on Disc icon on the right side. It will prompt you where to save the package. Save it in the same project folder which you made at the initial stage (we saved on the desktop). It will create the package for the project as shown in Fig. 9.

After the package has been created, go to the project folder where you saved your project. Open that project folder and you will find 'pkg' command file. Double click on that command file and you will see Running MCR Installer on the command window and installation box as shown in Fig. 10.

Install it as shown in Fig. 11. MATLAB Compiler Runtime gets installed as shown in Fig. 12.

When installation is completed, click on your project command file and, after a few seconds, you will see the GUI of your project as shown in Fig. 2.

Standalone MATLAB application runs without the help of the MATLAB interpreter. In fact, the applications can run even if the

MATLAB software is not installed on the system. By using this standalone MATLAB application, you need not depend on the costly licence version of MATLAB. ●

The author is a B.Tech in electronics and communications from SRCEM College, Gwalior