



297-compliant SFD 1856 and MO-300-compliant mSATA A1 to meet the need for industrial mobility devices. The small size equipped with SATA 3.0 high-speed transmission interface, along with the products' features of low-power consumption, durability and high performance, will become the necessary storage solution for the rise of the new mobility devices. It can be specially applied to medical tablet PCs, bedside healthcare, mobile on-board unit and data communication system devices.

Apacer Technologies Pvt Ltd, Bengaluru
Phone: (080) 41529061/62/63
E-mail: india_sales@apacer.com
Web: www.apacer.com

Bluetooth thermal printer

NGX Technologies has launched a Bluetooth thermal printer, BTP110, which supports Windows and Android OS. It offers low power consumption and its specifications include speed of 50mm/second, 203DPI (8dot/mm) resolution, 58mm

width, 48 characters per line, 0.065mm-0.086mm thickness, maximum roll diameter of 50mm, inner diameter of 12.5±0.5mm. This thermal printer is powered by a high-capacity 7.4V Li-ion, 1600mAh battery and comes with baud rate adjustment to 9600.

NGX Technologies Pvt Ltd, Bengaluru
Phone: (080) 40925507
E-mail: sales@ngxtechnologies.com
Web: www.ngxtechnologies.com

Dual-head 3D printers

Aha 3D Innovations has launched ProtoCentre 999 series dual-head 3D printers. Designed for the quality-conscious users, the ProtoCentre 999 and the ProtoCentre 999Duo rapid prototyping machines

feature dual extruders, which enable the use of separate support material so you can fabricate an object of almost any geometry. These machines are designed with a focus on build speed and quality, and feature reliable all-metal extruders,



all-aluminium chassis and low moving mass design to enable fast print moves. As a world's first, these machines ensure

the build does not get wasted if a power cut happens while in operation.
Aha 3D Innovations Pvt Ltd, Jaipur
Phone: +91-9929904445
E-mail: info@aha3d.in
Web: www.aha3d.in

COMPONENTS

Thermal circuit breaker series

Schurter Electronics has expanded T9 fuseholder-style thermal circuit breaker series to include Model T9-818 for PCB mounting. The new model complements the existing T9 series assortment for panel mounting, providing a complete range of mounting styles equivalent to closed fuseholders.

The T9 series features dimensions comparable to those of traditional fuseholders and is similarly designed for direct placement on circuit boards. Schurter's existing T9 series features quick connect terminals for front and rear snap-in-panel mounting, as well as a threaded neck mounting style. Typical application areas include



UPS systems, PDU's, electric tools, use in power supplies, industrial applications, medical diagnostic equipment, analysis systems, lighting fixtures, HVAC products as well as equipment for sports and leisure activities.

Schurter Electronics (India) Pvt Ltd, Gujarat
E-mail: sales@schurter.co.in
Web: www.schurter.co.in

High-speed data converters

Semtech Corporation has announced ultra-high-speed ADC and DAC for advanced communication systems. These converters enable agile operation and concurrent multi-band/multi-beam operation as well as extremely high dynamic performance, ideally suited for highly oversampled systems utilising large instantaneous bandwidth at low power and in small areas. The ADC cores have an area of 4 mm² and the DAC cores have an area of 2.2 mm². They include a wide tuning millimetre-wave synthesiser, enabling the core to tune from 42 to 68GHz/s per channel with a nominal jitter value of 45 femtoseconds root mean square.

CoreEL Technologies (India) Pvt Ltd, Bengaluru
Phone: (080) 41970400
E-mail: sales@coreel.com
Web: www.coreel.com

Ambient light sensor

Maxim Integrated has introduced Santa Cruz (MAXREFDES23#) ambient light sensor. With this, factories can quickly configure and monitor multiple red, green, blue (RGB) and infrared (IR) ambient light sensors with the high accuracy required in industrial applications. This reference system provides a wide, dynamic range of clear, RGB and IR light and temperature data. Santa Cruz is tuned to the response of the human eye for accurate system function relative to



visible light. In addition, it is unsurpassed for light sensitivity and low latency. The integrated IO-Link software and device stack automatically configure the sensor without additional programming, saving valuable time and resources. Additionally, Santa Cruz fits on a tiny 6.5mm x 25mm printed circuit board (PCB), making it the industry's smallest ALS system.

Maxim Integrated Products, Inc., Bengaluru
Phone: (080) 30285800
E-mail: sales@maximintegrated.com
Web: www.maximintegrated.com