

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

TEST & MEASUREMENT

Vector signal generator

Rohde & Schwarz presents its new R&S SGT100A, the smallest and fastest vector signal generator that covers the frequency range from 80MHz to 6GHz. Specially optimised for use in production test systems, it is equipped with an integrated baseband generator that supports a maximum bandwidth of 160MHz. Using the R&S WinIQSIM2 PC software, the generator can quickly



and easily deliver test signals for all major digital standards such as LTE, 3GPP and WLAN IEEE 802.11ac.

Featuring frequency and level switchover times of typically 240µs, the R&S SGT100A is the fastest instrument of its type on the market. The short switching times of just a few micro-seconds between the various digital test signals speed up test sequences. In addition, the instrument has been optimised for minimum operating costs.

Rohde & Schwarz India Pvt Ltd, New Delhi

Phone: 011 42535400

E-mail: customersupport@rohde-schwarz.com

Vector network analyser

Anritsu introduced the MN469xC test set for its VectorStar MS4640B vector network analyser (VNA) family that comes with the inherent advantages of the VectorStar platform, including one of the industry's best frequency coverage, True Mode Stimulus (TMS) accuracy and performance, and 4-port measurement applications. The 4-port VectorStar provides active device engineers with signal integrity and best-in-class measurement results for improved simulation tools and greater confidence in differential device designs. Engi-



neers can use the 4-port VectorStar to conduct detailed TMS differential analysis from 70kHz up to 145GHz in a single sweep using Anritsu's proprietary DifferentialView, which offers the ability to provide a calibrated TMS signal to differential devices and has the capability to sweep phase for full analysis of devices.

Anritsu Corporation, Bengaluru

Phone: 09310666466

Website: www.anritsu.com

Inspection system

Omron launched a new inspection system using 3D measurement, called VT-S500, which is Omron's solution to providing next-generation, 3D inspection capability at minimal cost. With good 3D image processing, the VT-S500 accurately analyses the topographical features of solder fillets to ensure PCB quality and reliability. Advanced software, capable of absorbing production inconsistencies and noise, creates adaptable and stable inspection programs. By minimising program teaching and



tuning times, the VT-S500 greatly reduces the inspection costs traditionally associated with automated optical inspection (AOI). With ultra high-speed inspections and dual-lane availability, cycle times have reduced and productivity has increased. The VT-S500 is available with camera magnifications of 10 or 15 microns, and is capable of processing PCBs up to 510 mm×610 mm (in single-lane applications) or 510 mm×300 mm (in dual-lane applications).

Omron Electronics, Mumbai

Phone: 022-71288400

Website: www.omron-ap.co.in

High voltage insulation testers

Metrel has launched the MI 3200 Tera Ohm 10kV, a digital diagnostic insulation tester. It enables high insulation resistance measurements up to 10TΩ, step voltage tests, PI, DD and DAR calculation, capacitance measurement and withstands voltage tests. The large LCD screen enables real-time graphs to be displayed. Results can be stored and downloaded to a computer via USB



or RS232 connection with the help of the optional software. Major applications include testing insulation resistance of rotating machinery, cables, transformers, HV generators, surge arresters, and effective measurements in high-noise environments such as charged sub-stations and switchyards.

Rishabh Instruments Pvt Ltd, New Delhi

Ph: 0253-2202202/028

E-mail: tmi@rishabh.co.in

COMPONENTS

Coil driver ICs

Intelligent coil-driver ICs for mono- and bi-stable EM actuators with 8V to 36V supplies launched by iC-Hauz GmbH are available through its India sales partner Omniscent Electronics. The 32-bit output driver, iC-DY6818,



features a serial SPI interface for the controls via a 3.3V or 5V microcontroller. The integrated 32-bit shift register performs the conversion from serial to parallel. A received 32-bit data word is uploaded to an internal register, which then operates the 32 push/pull