

output drivers. The output drivers' separate supply V_{BB} can range from 8V to 36V. The adjustment to typical industrial 24V signal levels is thereby provided. Further, mono- and bi-stable relays, valves, solenoids, small DC motors, as well as LED chains can easily be controlled.

Omniscient Electronics Pvt Ltd, Bengaluru
Phone: 080-28611874/950
E-mail: info@omniscientelectronics.com

Data converter

Maxim Integrated launched a flexible data converter, which is ideal for base stations, industrial control and automation. Engineers can mix and match 20 ADCs, 20 DACs or 20 high-voltage digital I/O pins in any order using the MAX1300 with the new mixed-signal PIXI technology. It is the industry's first configurable 20-channel, -10V to +10V high-voltage mixed-signal data converter. It is ideally suited for complex applications requiring multiple mixed-signal operations like base stations, and industrial control and automation. Graphical user interface software that comes with the MAX1300 PIXI allows rapid drag-and-drop configuration of the device.

Maxim India Integrated Circuit Design Pvt Ltd, Bengaluru
Phone: 080-79415800
E-mail: sales@maximintegrated.com

Buck converters

Texas Instruments has introduced 18V, 20A and 30A synchronous DC/DC buck converters with the PMBus interface. The SWIFT TPS544B20 and TPS544C20 converters feature small QFN packages and integrated MOSFETs to drive ASICs in space-constrained and power-dense applications in various markets, including wired and wireless communications, enterprise and cloud computing, and data storage systems. The converters simplify power conversion and speed the power supply design process. The highly integrated converters feature 0.5% reference voltage accuracy and fully differential remote voltage sensing to meet voltage requirements of



feature current and temperature monitoring also.

Texas Instruments, Bengaluru
Phone: 080-25586277
Website: www.ti.com/ucvfin/

Backplane connectors

FCI announces the ExaMAX high-speed backplane connector family. These high-speed connectors are designed to deliver superior 25Gb/s electrical performance while offering a migration path to 40Gb/s. These also feature a revolutionary beam-on-beam contact interface. They minimise the residual stub for improved signal integrity performance, compared to typical blade-on-beam contact structures and provide exceptionally low mating force while maintaining excellent contact.

The ExaMAX portfolio is available in 2-pair, 3-pair, 4-pair and 6-pair versions with various column counts.

Interface Connectors Pvt Ltd, Bengaluru
Phone: 080-23374772, 23374773, 23374774
E-mail: sales@icpl.co.in

Diode arrays

Littelfuse has introduced the SM24CA-NA series of 200W TVS diode arrays for protecting the automotive controller area network (CAN) bus from damage due to electrostatic discharge (ESD), electrical fast transients, and other over voltage transients. These arrays absorb repetitive ESD strikes above the maximum level specified in the IEC61000-4-2 international standard without performance degradation. They safely dissipate 3A of surge current with very low clamping voltages. These AEC-Q101 qualified devices help to maximise the reliability of automotive electronics applications like drive-by-wire (CAN



deep sub-micron processors. The 20A and 30A SWIFT DC/DC buck converters

BUS) systems, engine control modules, powertrain electronics, anti-lock brakes, airbags and other safety circuits. They are also suitable for use in industrial CAN bus applications that are susceptible to damage due to lightning-induced transients or ESD.

Littelfuse, Noida
E-mail: woinaik@littelfuse.com

Super pulse capacitors

EVE Energy launched its super pulse capacitors that can store and discharge pulse current within a temperature range of -40°C to +85°C. It is the ideal power source for long-term standby and high current pulse applications. EVE's unique design is based upon the latest technology to ensure safety and reliability.

SM Electronic Technologies Pvt Ltd, New Delhi
Phone: 011-25101136
E-mail: sales@mysmindia



SOLAR

Multi-purpose solar lantern

Gautam Solar launched its unique solar multi-purpose lantern across India. Designed for urban users, the product is a trailblazer, and can be used as a torch, a hanging light, a study lamp and a mobile charger. The lantern is fitted with 3W LED lights, a 3W solar panel and 6 V-4.5AH battery that requires four to five hours of charging. Once charged, the lantern can effortlessly run for eight hours on single brightness, six hours on medium brightness and four hours on full brightness. The lantern is available in two trendy colours—yellow and red—to spruce up any corner of your home or office.

Gautam Solar Pvt Ltd, New Delhi
Phone: 1800-532-0800/09313314063
E-mail: solarlights@gautampolymers.com

