

Global lithium battery manufacturer Energy solution provider

EVE
ENERGY VERY ENDURE



Model	Referen Model	Nominal Voltage(V)	Nominal Capacity(mAh)	Maximum Continuous Current(mA)	Maximum Pulse Current(mA)	Operating Temperature(°C)	Maximum Dimensions		Weight (g)
							Diameter(mm)	Height(mm)	
ER14250	1/2AA	3.6	1200	15	50	-60℃~+85℃	14.5	25.4	10
CR2032		3.0	225	3	15	-20℃~+70℃	20.0	3.2	3.1
CR2450		3.0	600	6	25	-20℃~+70℃	24.5	5.0	6.5

EVE ENERGY CO.,LTD.

Add: NO. 36 HuiFeng 7 Road, Zhangkai High
Technology Development Zone, Huizhou,
Guangdong, China
Tel: 0086-752-2606966
Fax: 0086-752-2601506
E-mail: sales@evebattery.com

Authorized Channel Partners in India

SM Electronic Technologies Pvt. Ltd.,
#1790, 5th Main, 9th Cross, RPC Layout,
Vijayanagar 2nd Stage, Bangalore - 560040
Contact Person: Mr. Rajiv Anand, Mob: +91-9810715377
Tel: +91-80 23301030 Fax: +91-80 23387197
E-mail: sales@mysmindia.com

PERFECT SOLUTIONS INC.
314, Krishna Mall, Sector-12,
Dwarka, New Delhi - 110075
Tel: +91-9213258888 Fax: +91- 45649530
Web: www.psiindia.com
E-mail: sales@psiindia.com
sources2004@gmail.com

RoHS

