



StrongIRFET™ Rugged, Reliable MOSFETs

Specifications

Package	B_{oss} (V)	ID @25°C (A)	$R_{DS(on)}$ max @VGS = 10V (mΩ)	Qg@ VGS = 10V (nC)	Part Number
POFN 5x6	25	100	0.95	56	IRFH8201TRPbF
	25	100	1.05	52	IRFH8202TRPbF
	30	100	1.1	58	IRFH8303TRPbF
	30	100	1.3	50	IRFH8307TRPbF
	40	100	1.4	134	IRFH7004TRPbF
	40	85	2.4	92	IRFH7440TRPbF
DirectFET Med.Can	40	85	3.3	65	IRFH7446TRPbF
	30	192	1.3	51	IRF8301MTRPbF
	40	90	1.4	141	IRF7940TRPbF
	60	114	3.6	120	IRF7980MTRPbF
D ⁺ -Pak	40	195	1.8	150	IRFS7437TRPbF
	40	120	2.8	90	IRFS7440TRPbF
	60	120	5.34	86	IRFS7540TRPbF
D ⁺ -Pak 7pin	40	195	1.5	150	IRFS7437TRPbF
	60	240	1.4	236	IRFS7530-7PP
D-Pak	40	90	2.5	89	IRFR7440TRPbF
	60	90	4	86	IRFR7540TRPbF
TO-220AB	40	195	1.3	300	IRFB7430PbF
	40	195	1.6	216	IRFB7434PbF
	40	195	2	150	IRFB7437PbF
	40	120	2.5	90	IRFB7440PbF
	40	118	3.3	62	IRFB7446PbF
	60	195	2.0	274	IRFB7530PbF
TO-247	40	195	1.3	300	IRFP7430PbF

Features:

- Ultra low $R_{DS(on)}$
- High current capability
- Industrial qualified
- Broad portfolio offering

Applications:

- DC Motors
- Inverters
- UPS
- Solar Inverter
- ORing or Hotswap
- Battery Packs

For more information, please visit us at www.irf.com or www.irf.com.cn

International
IOR Rectifier
THE POWER MANAGEMENT LEADER