



The AMC1304 delta-sigma modulator family offers best-in-class precision performance and the lowest power consumption with reinforced isolation for current shunt monitoring.

The ISO7842 family provides reinforced isolation with 8000V maximum transient overvoltage, according to standard DIN V VDE 0884-10. It has an isolation rating of 5700Vrms, according to standard UL 1577. High common mode transient immunity (CMTI) performance of 100kV/microsecond provides reliable communication in noisy environments. With the industry's highest surge voltage protection rating of 12,800 V_{PEAK}, the ISO7842 can withstand high instantaneous voltage pulses that can help protect electronics from damage by voltage spikes. The ISO7842 provides accurate timing with more than 100Mbps data rate and low jitter.

Key features of the AMC1304 family include an offset error maximum of 150 microvolts and gain error of ± 0.3 per cent, which is industry's best DC performance. Industry-leading AC performance allows motor control designers to minimise distortion and noise. The lowest power dissipation (maximum 7mA primary, and 5mA secondary side), together with 50mV input voltage range, reduces overall system power consumption by up to 80 per cent. Four AMC1304 delta-sigma modulators allow designers to connect the modulator to an unregulated supply voltage. When paired with TI's C2000 Delfino TMS320F2837x and TMS-320F2807x microcontrollers (MCUs) with integrated modulator interfaces and sine filters, AMC1304 can boost system performance by precisely and efficiently acquiring multiple analogue signals. The devices deliver reinforced isolation of 7000V, peak, surge voltage of 10,000V and working voltages of 1000Vrms and 1500V DC. These are UL recognised component to UL 1577 and certified to DIN V VDE 0884-10.

Texas Instruments
Website: www.ti.com

TEST & MEASUREMENT

Digital multimeter

MECO-G has introduced a series of handheld digital multimeters featuring



ing 3½-digit and backlit LCD display incorporating the latest technology. These digital multimeters can measure AC voltage, DC voltage, DC current, AC current, resistance, capacitance, temperature, battery

test voltage and frequency.

Additional features include diode test, transistor check, continuity check, low battery display, data hold and auto power-off. The multimeters have a built-in holster for anti-sliding, and are useful in various industries, manufacturing units and for domestic purposes too.

Goliya Instruments Pvt Ltd
Phone: 022-24149657
E-mail: sales@goliyainstruments.com
Website: www.goliyainstruments.com

Field analyser

Anritsu has introduced its first field analyser, MW82119B PIM Master with integrated PIM and line-sweep testing capabilities. It combines a 40W battery-operated passive intermodulation (PIM) analyser with a 2MHz to 3GHz cable and antenna



analyser, eliminating the need to carry multiple instruments to measure the RF performance of a mobile tower site.

The MW82119B provides tower and maintenance contractors, network installers and wireless service providers with the first handheld field PIM analyser with line-sweep capabilities so they can fully certify the cable and antenna systems at cell sites. There are nine models available in the MW82119B PIM Master family. Covering various bands and featuring unprecedented measurement capability, MW82119B PIM Master is well-suited for a number of applications, including deployment and maintenance of LTE remote radio heads (RRH), small cells and distributed antenna systems (DAS).

Anritsu India
E-mail: siiri.hage@anritsu.com
Website: www.anritsu.com

MISCELLANEOUS

LEDs

Kwality Photonics has launched a range of LM80-certified white-power



LEDs that include high-power 3535, medium-power 5630 and 2835, and low-power 3014 and 3528 LEDs.

The wide choice of LM80-certified Kwality Polywa' LEDs, namely, KLHP3535W (350mA), KLSL5630W (150mA), KLSL2835W (60mA), KLSL3014W (30mA) and KLSL3228W (20mA) LEDs, together can meet every possible design requirement, including LED street lights, LED tubelights and LED retro-fit bulbs.

Kwality Photonics Pvt Ltd
Phone: +91-9000081171
Website: www.kwalityphotonics.com