

Rubycon

RUBYCON CORPORATION

HIGH QUALITY & RELIABLE ALUMINUM ELECTROLYTIC CAPACITORS

Applications : UPS / Inverter / AC Drives / DC-DC Converters/
LED Drivers/ Power Supply Units



RUBYCON SINGAPORE PTE LTD (INDIA LIAISON OFFICE)

123, Dimple Arcade, Thakur Complex, Kandivali East, Mumbai - 400101
Tel: 022-28543154; Fax: 022-28543155, Mobile: 09820408945,
Email: chandramouli@rubycon.co.jp

SCREW TERMINAL TYPE

Temperature : 85°C/105°C
Life Hrs : 2000Hrs to 5000Hrs
Cap Value : 200uf to 880000uf
Voltage : 10V to 500V DC

SNAP-IN TYPE

Temperature : 85°C/105°C
Life Hrs : 2000 Hrs to 7000 Hrs
Cap Value : 22uf to 82000uf
Voltage : 10 V to 500V DC

RADIAL TYPE

Temperature : 85°C/ 105°C
/125°C/130°C/150°C
Life Hrs : 2000Hrs to 20000Hrs
Cap Value : 1uf to 33000uf
Voltage : 6.3 V to 500V DC

SMD TYPE

Temperature : 105°C / 125°C
Life Hrs : 2000Hrs to 5000Hrs
Cap Value : 1uf to 10000uf
Voltage : 6.3 V to 100V DC

www.rubycon.co.jp

LED LIGHT HOUSING AND ACCESSORIES

GRID / FALSE CEILING

40 W, 60 W, 100 W Size : 595 X 595 mm
15 W, 36 W Size : 300 X 300 mm

FOCUS / TUNNEL / PETROL BUNK/STREET LIGHT



70W



105W



140W



BURIAL / UNDERGROUND LIGHT

1W, 3W

C.O.B DOWN LIGHT:



SUITABLE FOR
6 W, 9 W, 16 W, 18 W & 24 W



QUALITY WITH ATTRACTIVE PRICES

SURFACE MOUNT FIXTURE



1W, 3W

MCPCB, DRIVERS, WATER PROOF CONNECTORS & SOLAR CONNECTORS

FAR EAST ELECTRONICS

85, DEVELOPED PLOT, ELECTRICAL & ELECTRONICS ESTATE, PERUNGUDI,
CHENNAI - 600 096 Mobile : +91 98849 06113, +91 44-2496 7444 / 445,
E-mail: marketing@fareastelectronics.com, www.fareastelectronics.com



ISO 9001:2008 CERTIFIED



Industrial Loads
Range : 1KW - 300KW



Low Ohmic Power Resistor
Open Frame Axial & PCB Mounting
Range : 0.001 - 1 ohms Power : 0.5 W - 3 W
Tolerance : $\pm 5\%$, $\pm 2\%$, $\pm 1\%$



Resistors Adjustable / Fixed
(Silicone Coated)
Range : E 001 - 500 K. Power : 0.5 W - 5000 W
Tolerance : $\pm 5\%$, $\pm 2\%$, $\pm 1\%$



Resistors Ceramic Encased
Range : E 001 - 100 K
Power : 2 W - 50 W
Tolerance : $\pm 5\%$



Resistors Aluminum Housed
Range : 0.1 ohms - 100 K ohms
Power : 5W - 1000 W
Tolerance : $\pm 5\%$



Dynamic Breaking Resistor
Range : E1 - 100 K
Power : 40 W - 10000 W
Tolerance : $\pm 5\%$



Rheostat (Open / Covered / LSM)
Range : 0.5 ohms - 10000 ohms
Power : 0.1 Amp - 200 Amp



Potentiometer (Single / Gang Type)
Range : 0.1 ohms - 10 K ohms
Power : 25 W - 1000 W
Tolerance : $\pm 5\%$

STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office : 1681/20, Mangal Market, Bhagirath Palace, Delhi-110006

Ph. : 23865929, 23862576 Fax : 011-23867465

Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7

e-mail : sales@steadresistors.com visit at www.steadresistors.com