

Communication made easy with USB MCU

Android Open Accessories with BC1.2 protocol

Renesas MCU series for USB support Android™ Open Accessories(AOA) which enable USB communication with Android-powered device, allow data transfer and control between Android-powered device and external USB hardware.

Applications

Industry, sensor data acquisition for health-care, and Android coordination with white goods


Benefits

- USB 2.0 Full speed interface, compliant with battery charging specification 1.2
- Communicate with Android devices as a USB host
- Supply 5V charging power to Android devices
- Use "Android Accessory Protocol"
- Use bulk transfer in USB data communication

External USB Hardware (Accessory)



USB Host



Android-Powered Device



USB Peripheral



- RL78/G1C Group MCU. Industry's First Low-Power 16-bit MCU with integrated USB
- Enables High-Speed charging BC 1.2 Standard whilst reducing system power consumption by up to 60%.
- RL78 16-bit 24 MHz (31 DMIPS) core
- ($\pm 1\%$) on-chip oscillator (accurate over operating temperature)
- 2.4V to 5.5V operation
- Small package options: 32-pin WQFN (5 x 5 mm), 48-pin WQFN (7 x 7 mm)



- RX111 Group MCU. High performance ultra-low power consumption 32-bit MCU with integrated USB2.0 host/ function controller and an OTG communication peripheral.
- RX 32-bit 32MHz 50DMIPS core 3.08 CoreMark/MHz
- Fast wake-up (4.8 μ s) from standby mode to run mode
- World's lowest current performance ratio (14.9CoreMark/mA)
- Low current consumption (0.1mA/MHz) in run mode
- Low standby current (0.35 μ A) without power shutdown
- Small package option : 36-pins WFLGA (0.5 mm pitch, 4 x 4mm)
- Wide Memory size from 16K to 512K* available

Note*: 256K ~ 512K version under development

Renesas Electronics India Pvt. Ltd.



<http://in.renesas.com/usbmdu>

RENESAS