

COMPONENTS

Automotive diode

Littelfuse has introduced the SLD series TVS diode for automotive and high-reliability applications. It offers circuit designers the freedom to upgrade their circuit protection in their existing design footprint or provide more robust load dump protection for new projects.

Following are the key benefits:

1. Meets international standards of the automotive industry
2. AEC-Q101 qualified with a junction temperature (Tj) up to 175°C
3. Compact footprint of the industry-standard P600 package
4. Both uni-directional and bi-directional polarity devices offer 10V to 60V standoff voltage

Littelfuse Inc.

Website: www.littelfuse.com

Ultrasonic distance sensor

RhydoLabz ECHO-PRO ultrasonic distance sensor provides very short to long-range detection and ranging with a resolution of 1mm. The five-in-one sensor module outputs distance data as serial ASCII, pulse width and analogue output. It has an onboard temperature sensor, which outputs the

ambient temperature via serial ASCII. The module is also equipped with proximity sensing output, which generates a high-going signal if an object comes under the presented distance range (2-500cm). Some key features are:

Output. Serial ASCII, pulse width, analogue, temperature output, proximity detector



Range. 2cm to 500cm

Modes. Auto and manual

Resolution. 1mm (PWM, ASCII)

Adjustable proximity range. Done

by Trim pot

Reading rate. 10Hz

Operating voltage. 3.0V-5.5V

Current. <20mA

Operational temperature. 0°C to +65°C

6-pin header. For easy connectivity, using a servo extension cable; no soldering required

Rhydo Technologies Pvt Ltd

Websites: www.rhydolabz.com,

www.rhydo.com

MOSFET

Toshiba has introduced the first 800V power MOSFET based on its high voltage DTMOS IV super junction technology. The TK17A80W uses Toshiba's state-of-the-art single-epitaxial process and is ideally suited to equipment that requires high reliability, power efficiency and a compact design.

Toshiba India

Website: www.toshiba.semicon-storage.com

TEST & MEASUREMENT

Power analyser

The new Dranetz HDPQ line features best-in-class communication, ground-up focus on operator safety, remote control and set-up, recording and reporting features, higher resolution measurements with faster sampling rates, high-definition user interface and a rugged package. Some other features are:

1. 1kV CAT III (arc flash safety), innovative hook-up and lead management scheme for voltage and current inputs, remote communications/Apple and Android apps/VNC
2. Higher sampling rates and improved data resolution



3. Tablet-like GUI, icon driven, taskbar shortcuts, dashboard and intelligent answer modules
4. Real-time reporting

The HDPQ product line comprises three models: Dranetz HDPQ Visa, Dranetz HDPQ Guide and Dranetz HDPQ Xplorer.

Cyronics Instruments

Website: www.cyronics.com

Electro-magnetic field measurement system

Anritsu's electro-magnetic field (EMF) measurement system is designed to measure radiation compliance with various national standards for personal safety set by governmental regulatory authorities.

Features of the EMF system are:

1. Limit lines are user-settable at various power levels across the spectrum
2. Limits can be saved for recall at a later time
3. Axis dwell time is user-settable (time that each axis [X, Y, and Z] measures radiation before switching to next axis)
4. Pass/Fail indicators on screen for immediate feedback on test results
5. Automatic save feature for easy storage of measurement results to internal memory (auto-logging) or USB stick
6. Results provided for maximum, minimum and average of all measurements conducted
7. Measurement time is user-configurable
8. Pre-am standard for measurements of low-level signals (optional for MS2711E)

Anritsu India Pvt Ltd
Website: www.anritsu.com

