

Calibrator

MECO's 90A universal calibrator has a 5½-digit LED display, which can display the actual value or percent-



age of full-scale (FS) range. One can select the voltage, current, frequencies and resistance with the help of knobs on the front panel to adjust the magnitude of output signals. It comes with a key adjuster for step adjustment of output signals. The basic accuracy of MECO 90A is $\pm(0.03\%RD + 0.02\%FS)$ for DC voltage.

Meco Instruments Pvt Ltd
Website: www.mecoinst.com

LED LIGHTS

Chip-on-board LEDs

EVERLIGHT's high-power (36W) XUAN COB series offers the dual benefit of high efficiency and easy assembly. Covering a wide wattage range at customers' preference from 2-50W, the MCP-CB device can achieve $>130lm/W$. It is designed with a high thermal-conductive mirror-aluminum substrate.

Its wide driving-operation range ensures a super-high efficacy in the typical driving state. In an over-driven state, however, it can deliver a high lumen output and, with a proper heat sink, remain stable to bring about an economic lighting design.

EVERLIGHT Electronics Co. Ltd
Website: www.everlight.com

LED industrial lights

Pyrotech offers a complete range of energy-saving LED industrial lights with optimum thermal management and highly-efficient con-



stant current driver, having short-circuit and open-circuit protection in die-cast aluminium housing. With these lights you can save up to 80 per cent power. The power factor is >0.9 and the housing is explosion proof.

Pyrotech Electronics Pvt Ltd
Website: www.pyrotechlighting.com

POWER SUPPLY

Photovoltaic power supply

MORNSUN PVXX-27BxxR2 series is particularly designed for photovoltaic industry due to its ultra-wide input-voltage range that can get power from solar panels



directly. These products feature a wide-operating temperature range, high-isolation voltage and multiple protections that ensure stability of the power supply.

Some features are:

Input voltage range. 100V DC ~ 1000V DC

Operating temperature range. $-40^{\circ}C \sim 70^{\circ}C$

High-isolation voltage. 4000V AC

MORNSUN India
Phone: +91-9820194705

E-mail: sunil@mornsun.cn
Website: www.mornsun-power.com

UPS system

Makvolt has launched an on-line double conversion DSC based UPS system, with capacities of 1kVA/800W, 2kVA/1600W, 3kVA/2400W and 5kVA/4000W.

It has single-phase input and frequency of 47Hz to 53Hz. It is fully DSC controlled. Other features of the product include an in-built galvanic isolation transformer, advanced PFC technology, short-circuit and over-load protection, LCD/LED display, EMI/RFI



noise filter, smart RS232 interface and static in-built bypass, among others.

Makvolt Power Pvt Ltd
Website: www.Makvolt.com

MISCELLANEOUS

Hooters

Shavison has launched hooters, which are available in three basic



sizes, 72x72mm, 96x96mm and 144x144mm. Supply voltages available are 230V AC, 24V DC and universal supply voltage (20V AC to 240V AC, or 12V DC to 240V DC). These are available in two tones and four tones.

Shavison Electronics Pvt Ltd
Website: www.shavison.com

USB 3.0 flash drive

Apacer's newly-launched AH154 USB 3.0 flash drive has a compact



and light body, with IPX7 waterproof features, as well as dustproof and anti-shock characteristics, to protect each piece of memory against any accidents. It is available in four capacities, 8GB, 16GB, 32GB and 64GB.

Apacer Technologies Pvt Ltd
Website: www.apacer.com

Server

With COMSOL server, applications can now be distributed throughout