

# Metrix+™

Innovative Excellence

## MT 10A

Infrared Thermometer  
-50~1000°C High Accuracy alarm set adjustable emissivity DS Ratio: 20:1



## MT 22

Infrared Thermometer  
200~2500°C High Accuracy alarm set adjustable emissivity DS Ratio: 80:1



**NEW**

4250T True RMS  
INRUSH 3% 3999  
AC/DC A/C/D/C  
Volt, Resistance,  
Capacitance,  
Frequency,  
Temperature,  
Continuity, Diode.



2250T True RMS  
INRUSH 3% 3999  
AC/DC Volt,  
Resistance,  
Capacitance,  
Continuity, Diode,  
Frequency,  
Temperature APO



**Metrix+ 130**  
Metal Hardness  
Tester HB, HRC,  
HRB, HRA,  
HB, HV, HS



**NEW**

Vibration  
Meter VB 8202A  
Acceleration,  
Velocity  
Displacement  
& Frequency



MT 4A Infrared  
Thermometer 600°C  
High Accuracy alarm  
set adjustable  
emissivity



**ULTRASONIC  
THICKNESS  
GAUGE**  
Mod: UTG 27  
Measuring range:  
1~400mm 0.1/0.01  
switchable, metric/  
imperial Combine, P/C  
Interface compatible

## minoo Impex

41, N.S.Road, 206, Anand Jyoti, KOLKATA 700061, INDIA.  
Tel: +91 33 2230 9888 Fax: +91 33 22309719, E-mail: [minooimpex41@vsnl.net](mailto:minooimpex41@vsnl.net)  
[metrixinstrument@gmail.com](mailto:metrixinstrument@gmail.com), [www.minooimpex.com](http://www.minooimpex.com)

**PUNE OFFICE Metrixplus Instruments (Pune)**

G7 Atharva Feryez Plaza, Opp: Shankar Maharaj Math, Pune-Satara Road,  
PUNE 411043, Maharashtra. Tel: 020 24379992 Mobile: 93717 74842,  
e-mail: [metrixinstruments@yahoo.com](mailto:metrixinstruments@yahoo.com), [metrixplus@hotmail.com](mailto:metrixplus@hotmail.com)

**CHENNAI DISTRIBUTORS Mehta Doshi & Company**

Tel: 044 25341892/65424041, Fax: 044 25332519  
E-Mail: [mehtadoshi@gmail.com](mailto:mehtadoshi@gmail.com), Web: [www.mehtadoshi.com](http://www.mehtadoshi.com)

# IND-SPHINX

PCB DRILLS | PCB ROUTERS

PCB SPECIAL TOOLS



Proudly  
Made in India  
Since 1989



Diamond Coated Tools

www.indspinx.com  
+91 1792 232860 / 232990  
customerfocus@indspinx.com

QUALITY • PRECISION • CONSISTENCY




ISO 9001:2008 CERTIFIED



Industrial Loads  
Range: 1KW - 300KW



Resistors Aluminum Housed  
Range: 0.1 ohms - 100 K ohms  
Power: 5W - 1000 W  
Tolerance: ±5%




Low Ohmic Power Resistors  
Open Frame Axial & PCB Mounting  
Range: 0.001 - 1 ohms Power: 0.5 W - 3 W  
Tolerance: ±5%, ±2%, ±1%



Dynamic Breaking Resistor  
Range: E1 - 100 K  
Power: 40 W - 10000 W  
Tolerance: ±5%



Resistors Adjustable / Fixed  
(Silicone Coated)  
Range: E 001 - 500 K Power: 0.5 W - 500 W  
Tolerance: ±5%, ±2%, ±1%



Rheostat (Open / Covered / LSM)  
Range: 0.5 ohms - 10000 ohms  
Power: 0.1 Amp - 200 Amp



Resistors Ceramic Encased  
Range: E 001 - 100 K  
Power: 2 W - 50 W  
Tolerance: ±5%



Potentiometer (Single / Gang Type)  
Range: 1 ohms - 10 K ohms  
Power: 25 W - 1000 W  
Tolerance: ±5%

## STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office : 1681/20, Mangal Market, Bhagirath Palace, Delhi-110006  
Ph. : 23885929, 23882576 Fax : 011-23867465  
Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7  
e-mail : [sales@steadresistors.com](mailto:sales@steadresistors.com) visit at [www.steadresistors.com](http://www.steadresistors.com)