

Latest Handheld Devices Available in the Market

Product	Model	Vendor	Form factor	Integration	UI	Power	Ruggedness	Connectivity
Base station analyser	BTS Master MT8220T	Anritsu	315x211x77mm 4.6kg	Two-port cable and antenna analyser, spectrum analyser, power meters (with external sensor), GPS receiver with antenna, bias tee, interference analyser with mapping, channel scanner, vector signal generator, signal analysers	213mm touch screen Backlit keyboard Night vision, high-contrast and black and white modes	7500mAh Li-Ion Lasts 2.5 hours	Operating temperature: -10°C to +55°C Humidity: 85% RH, non-condensing Shock: MIL-PRF-28800F class 2 Storage: -51°C to +71°C Altitude: 4600m Explosive atmosphere: MIL-PRF-28800F section 4.5.6.3 MIL-STD-810G, method 511.5, procedure 1	Ethernet, USB cable, and USB memory stick
Cable and antenna analyser	Site Master series	Anritsu	273x199x91mm 2.71kg	Cable and antenna analyser, spectrum analyser Optional: Two-port transmission measurements, interference analyser with interference mapping, power meter, coverage mapping, channel scanner, GPS, AM/FM/PM analyser	Menu-driven touch screen UI Built-in touch-screen keyboard Daylight-viewable display	7500mAh Li-Ion Lasts 4.5 hours	Operating temperature: -10°C to 55°C Humidity: 95% RH, non-condensing at 40°C Shock: MIL-PRF-28800F class 2 Storage: -40°C to 71°C Altitude: 4600m	Ethernet, USB cable or USB memory stick
Microwave spectrum analyser	FieldFox series	Keysight	292x188x72mm 3kg	Spectrum analyser Optional: Full-band tracking generator, full-band pre-amplifier, interference analyser and spectrogram, reflection measurements, built-in power meter, pulse measurements	165mm transfective, back-light display Softkeys	Lasts 3.5 hours	Operating temperature: -10°C to +55°C Humidity: 95% Altitude: 9144m MIL-PRF-28800F class 2 Explosive atmosphere: MIL-STD-810G, method 511.5, procedure 1	USB, LAN, SD card slot USB keyboard and mouse support, app for remote display
Modulation analyser	LMR Master S412E	Anritsu	273x199x91mm 3.6kg	Cable and antenna analyser, spectrum analyser, NBFM signal analyser with coverage mapping, LMR signal analysers with coverage mapping, broadband signal analysers, interference analyser with interference mapping, internal power meter, optional external power sensor	Daylight-viewable colour touch-screen display	7500mAh Li-Ion Lasts 3.6 hours	Operating temperature: -10°C to 55°C Humidity: 95% RH (non-condensing) at 40°C Shock: MIL-PRF-28800F class 2 Explosive atmosphere: MIL-PRF-28800F, Section 4.5.6.3 MIL-STD-810G, method 511.5, procedure 1 Storage: -40°C to 71°C Altitude: 4600m	USB cable, USB Memory Stick
Passive intermodulation (PIM) analyser	PIM Master MW821198	Anritsu	350x314x152mm 9.2kg to 12.4kg	Optional: Cable and antenna analyser, GPS, power meter	213mm daylight-viewable touch screen Built-in touch-screen keyboard	Li-Ion Lasts three hours	Operating temperature: -10°C to 55°C Storage temperature: -51°C to 71°C Humidity: 95%, non-condensing Ingress protection (IP): IP54, IP67 when enclosed in optional transit case Shock: MIL-PRF-28800F class 2, (30g half-sine, six shocks each axis, while operating) Transit drop: MIL-STD-810G, method 516.5, procedure IV, 122cm (48-in) drop height, each face, edge and corner, (26 drops total), in soft carry case. Altitude: 4600m	USB cable, USB Memory Stick
RF and microwave analyser	FieldFox series	Keysight	292x188x72mm 3kg	Cable and antenna analyser Optional: Spectrum analyser, vector network analyser, vector voltmeter, built-in power meter, pulse measurements	165mm transfective, back-light display Softkeys	Lasts 3.5 hours	Operating temperature: -10°C to +55°C Humidity: 95% Altitude: 9144m MIL-PRF-28800F class 2 Explosive atmosphere: MIL-STD-810G, method 511.5, procedure 1	USB, LAN, SD card slot USB keyboard and mouse support, app for remote display
Spectrum analyser	FSH13 and FSH20	Rohde & Schwarz	194 x 300 x 144mm 2.5kg	Internal tracking generator and VSWR bridge with built-in DC voltage supply (bias), pre-amplifier, vector voltmeter. Optional: Power meter, cable and antenna tester and a two-port vector network analyser	145mm transfective display	AC supply 6750mAh NiMH, lasts four hours	Operating temperature: 0°C to +50°C Storage: -20°C to +60°C Humidity: 95% at +40°C Vibration (sinusoidal): EN 60068-2-1, EN 61010-1 Vibration (random): EN 60068-2-64 Shock: EN 60068-2-27	RS-232-C optical interface
Spectrum analyser	RSA306	Tektronix	30.5x190.5x127mm 0.59 kg	General-signal analysis, analogue modulation analysis, RF measurements	SignalVu-PC software API for Microsoft Windows environment MATLAB instrument driver for use with instrument-control toolbox	Provided by host PC via USB	Pollution degree 2. Rated for indoor, dry location use only.	USB
Transport tester	Network Master Pro MT1000A	Anritsu	257x164x77mm 2.7kg	Metro and core networks OTN installation and maintenance, carrier class Ethernet installation and troubleshooting, mobile back-haul installation and verification, storage area networking (SAN) testing, SDH/SONET and PDH/DSn networks testing	229mm active thin-film transistor (TFT) touch-screen display	Li-Ion Lasts four hours	Operating temperature: 0°C to +50°C (non-condensing)	WLAN, Bluetooth, USB, Ethernet
Transport tester	Network Master Flex MT1100A	Anritsu	320 x 225 x 82mm 3kg	Transport tester supporting simultaneous installation of four independent 100Gbps ports and displays results in single screen, detailed client-signal analysis using Ethernet frame capture Support various OTN mappings including ODUflex FEC performance tests	307mm active matrix TFT touch-screen display	Li-Ion Lasts six hours	Operating temperature: 0°C to +40°C, <80% RH (non-condensing) Storage: -20°C to +50°C, <80% RH (non-condensing, with battery)	WLAN, Bluetooth, USB, Ethernet
Vector network analyser (VNA)	FieldFox series	Keysight	292x188x72mm 3kg	Transmission/reflection VNA Optional: Full two-port S-parameters, two-port QuickCal, time domain, cable and antenna analyser, vector voltmeter, built-in power meter, pulse measurements	165mm transfective, back-light display Softkeys	Lasts 3.5 hours	Operating temperature: -10°C to +55°C Humidity: 95% Altitude: 9144m MIL-PRF-28800F class 2 Explosive atmosphere: MIL-STD-810G, method 511.5, procedure 1	USB, LAN, SD card slot USB keyboard and mouse support, app for remote display