

THE LEADING RELAY R&D AND MANUFACTURING BASE GLOBALLY

Xiamen Hongfa Electroacoustic Co. Ltd is the first largest relay manufacturer in China and one of the leading relay manufacturers and suppliers in the world. It produces a wide range of products, including relays, low-voltage devices, precision components and automatic equipments. In particular, it has over 160 types of relay categories, including power relays, latching relays, automotive relays, signal relays, industrial & electrical appliance relays, safety & electrical appliance relays, solar relays and hermetically sealed relays, which provide over 40,000 regular-used relay specifications.

POWER RELAY

UPS, Inverter, Control panel, Voltage stabilizer



HF3FA (215)

- 1 pole: 15A 125VAC, 10A 250VAC/28VDC
- Product in accordance to IEC 60335-1 available



HF3FF (215)

- 1 pole: 10A 277VAC/28VDC



HF14FW(136)

- TV-8, 20A switching capability (1 pole configuration)
- 4kV dielectric strength
- Meeting VDE 0700, 0631 reinforce insulation

UPS, Inverter



HF105F-1(136)

- 40A switching capability
- 4kV dielectric strength (coil to contacts)
- Unenclosed, Plastic sealed and dust protected types available



HF102F

- Heavy load up to 5000VA
- Ideal for motor load
- (80A High inrush current)
- PCB & QC layouts available



HF33F

- 1 pole: 10A 125VAC, 5A 250VAC/30VDC
- Creepage distance: 8mm (NO to NC)
- High sensitivity 200mW available

Railways and Air-con.

Timers/Relay module

Lighting application

UPS

PLC Controller

Air-con.



HF46F

- 1 pole: 5A 277VAC/30VDC at 85°C
- Surge withstand voltage up to 10kV
- High sensitivity: 200mW



HF115FD

- 16A switching capability
- Creepage distance: 10mm
- Updated version of HF115F
- 1 pole equipped with automatic production line



HF49FD

- 3kV dielectric strength between coil and contacts
- 5mm size: width 5mm, height 12.5mm
- High sensitivity: min. 120mW



HF118F(136)

- 1 pole: 10A, 21V (2 pole): 5A
- dielectric strength: 5kV
- Creepage distance >8mm
- Reflow soldering available

Telecom, EPABX, Mobile tower



HFD27

- High contact capacity 2A 30VDC
- Matching 16 pin IC socket
- Epoxy sealed for automatic-wave soldering and cleaning



HFD23

- 1 Form C configuration
- 2A switching capability
- High sensitive: 150mW
- Plastic sealed type available



HFD3

- Surge withstand voltage up to 2500VAC, meets FCC Part 68 and Telecordia
- SMT and DIP types available
- Single side stable and latching type available

Control panel



HF18FF / HF18FH

- 7A switching capability (2C, 3C type)
- Various terminals, test button available
- Cole plated contact available
- 2 to 4 pole configurations



HF13F

- 15A switching capability (1 Form C)
- Conform to the CE low voltage directive
- 1 & 2 pole configurations
- Various terminals available

Authorized Distributor for Electronics Components



MILLENNIUM SEMICONDUCTORS

Corporate Office :

17/18/19, 2nd Floor, Mahalaxmi Heights, Mumbai-Pune Road, Pimpri, Pune 411 018, Maharashtra, INDIA, Tel/Fax : +91-20-2748 4800, 2748 4900, 2748 5000
Email: Kshitij@millenniumsemi.com, info@millenniumsemi.com

Sales Offices:

• Ahmedabad • Hyderabad
• Mumbai • Chennai
• Nashik • Coimbatore

Overseas Offices:

Singapore: 160, Paya Lebar Road, # 06-01, Singapore 409 022
China: # 1209, Giffery City, Jia-Hui-Xin-Cheng, FuMing Road, Fu Tian Dist., Shenzhen, China

Branch Offices :

Delhi: 202, 2nd Floor, Gupta Towers II, Near PVR Cinema, Vikaspuri, New Delhi 110 018, INDIA
Bangalore: 705, Oxford Tower, old Airport Road, Kodihalli, Bangalore 560008, INDIA