

achieves miniaturisation, higher ripple-current capability and lower impedance compared to YXF. It offers a smaller size, while maintaining the same or better capacitance, impedance, ripple current and lifetime specifications.

YXJ is best suited in the applications of smart meters that form the central function of a smart-grid system. The main features of this product are:

Size: $\Phi 5 \times 11L$ to $\Phi 16 \times 35.5L$

Temperature: -40°C to $+105^{\circ}\text{C}$

Rated voltage: 6.3V to 100V DC

Capacitance: 0.47 μF to 15000 μF

Lifetime: 4,000 to 10,000 hours

Rubycon India

Phone: 91-022-28543154

Website: www.rubycon.co.jp

TEST & MEASUREMENT

LED stroboscope

The Fluke 820-2 stroboscope is a simple, easy-to-use tool for investigating and observing potential mechanism failure on a variety of machinery without making physical contact with the machine. The rugged, compact strobe allows maintenance teams to identify the running speed of rotating equipment without stopping operation, and perform stop-motion diagnostics of parasitic oscillations, flaws, slippage and unwanted distortions. It also enables teams to identify serial numbers and other markings on fast-moving parts.

It features a seven-LED high-intensity array with uniform flash characteristics that allows for high flash rates from 30 to 300,000 flashes per minute. The solid-state LEDs have no filament, gases, hollow cavities or glass to compromise its rugged construction.

The adjustable flash-duration feature of the stroboscope is ideal for applications with higher rpm or larger rotating objects with high surface speeds, where objects may

move during the brief period of a single flashing, resulting in a blurred image. This feature allows users to decrease the flash duration making the image appears sharper.

Fluke Corporation

Website: www.fluke.com/india

Temperature sensor

The new AX8 fixed-mount temperature sensor from FLIR combines thermal and visible cameras along with FLIR's proprietary MSX technology in a small, affordable package. Enabled by FLIR's ground-breaking Lepton thermal imaging

core, AX8 provides early detection of temperature-related issues in electrical and mechanical equipment, guarding against unplanned outages, service interruptions and equipment failure.

AX8 thermal imager has 4,800 active temperature points per image, provides streaming temperature data over industry-standard interfaces (Ethernet/IP and Modbus TCP) for easy analysis, has a built-in web interface and includes a full suite of analysis and alarm functions that automatically send alerts when the AX8 detects elevated temperatures.

Measuring only 54 x 25 x 95mm, AX8 integrates easily into electrical installations or any manufacturing environment. Its streaming thermal, visual, and MSX video is output in standard MJPEG, MPEG, H.264 formats adds multi-purpose image capabilities.

FLIR Systems Inc.

E-mail: www.flir.com/ax8

Cable-fault pre-locator

KUSAM-MECO underground cable-fault pre-locator model KM-CFL-620 is an automatic fault locator that adopts ARM, FPGA and dot-matrix colour LCD display technology. It combines pulse-reflecting technology (TDR) and intelligent-bridge testing (Bridge) for measuring the exact location of the fault. It is a

microprocessor based fault locator with a user-friendly menu. It tests almost all power cables, telecom and signal cables. With a megameter and an ohmmeter, it allows insulation-resistance and loop-resistance tests. It has a USB port for uploading test data to the computer.

It comes with a carrying case, rechargeable battery charger/ adapter, connecting test cables, software CD, 4GB pen drive and user manual.

Kusam Electrical Industries Ltd


Phone: 91-22-24181649 / 24124540

E-mail: kusam_meco@vsnl.net



CAN analyser

A compact, isolated USB to CAN interface, CANdISO allows a PC to



be connected directly to an embedded CAN bus. The USB and CAN ports are separated

by a 500V galvanic isolation barrier. The analyser is fully-compliant with CAN 2.0A & CAN 2.0B Bosch specifications. It has ISO 11898-2 (high-speed CAN) physical interface, rugged CAN transceiver capable of withstanding 40V between CAN bus lines and ground, and CAN baud rate adjustable from 12.5k to 1M baud. It can recognise CAN data, remote and error frames, report CAN bus status and internal status, and calculate average CAN bus load every second. All CAN frames are time-stamped (25.6us resolution and 20ms + 100ppm accuracy).

The analyser supports three modes of CAN bus operation, namely, normal, listen-only and loopback; and low-level CAN message filtering. It is fully-compatible with higher-level protocols such as J1939, Device-Net and CANopen, and is USB v1.1, 2.0 and 3.0 compatible. It can be powered via USB ports (100mA max).