

in normal mode or 500µA max. in suspend mode). Its internal firmware is upgradeable from PC over USB. It complies with the requirements of EU directive 2004/108/EC on EMC.

Netronics

Website: <http://www.cananalyser.co.uk/candoiso.html>

Signal analyser

The Tektronix RSA306 is a compact, low-power spectrum analyser that is designed for portability. It can be used with laptops and tablet PCs that have a USB 3.0 connection, and draws all of its power (less than 4.5W) from that connection.

This analyser acquires samples using a fast digitiser and continuously updates spectra in the real-time acquisition bandwidth via a Fourier transform. Wider spans are generated by moving local oscillator



frequencies in the instrument and stepping in chunks of the real-time bandwidth to the desired frequency range. The basic specifications of RSA306 are:

Frequency range. 9kHz – 6.2GHz

Acquisition bandwidth. 40MHz

Measurement power range.

+20dBm to -160dBm

Spur-free dynamic range. -50dBc

Amplitude accuracy. ±2.0dB

Minimum signal duration. 100µsec

Operating temperature range. -10°C to +55°C

Weight. 590 grams

Tektronix

Phone: 080-30792726/41

Website: <http://www.tek.com/>

POWER SUPPLIES

Wireless charging solution

Bringing customers one step closer to the wireless Internet of Tomorrow, Freescale Semiconductor extended its wireless charging portfolio by introducing the industry's first 15W Qi-compliant wireless charging solu-

tion. This paves the way for ultra-fast wireless recharging for a variety of larger mobile devices, including tablets, large-screen smartphones, and portable industrial and medical equipment.

Delivering three times the power of common 5W charging solutions, this system provides efficient charging of larger form-factor devices with higher capacity batteries, while enabling faster charging of smaller form-factor devices by delivering higher power. For example, a typical tablet with 4000mAh battery might take over eight hours to charge from a standard USB port, while Freescale's solution could reduce this charge time dramatically to just a few hours.

Freescale Semiconductor Inc.

Website: www.freescale.com

Modular UPS

Delta Electronics has launched Modulon DPH series UPS 75/150kW, to join its existing 200kW model. It has a fully fault-tolerant design achieved by self redundancy of the power module with in-built control mechanism. Full-control logic allows the system to self-synchronise in case of failure and automatically switch to back-up to ensure continuous operation.

Modulon DPH is designed for seamless scalability for both

vertical and horizontal expansion. Scaling from 25kW up to 75/150/200kW, the UPS supports high flexibility for datacentre growth and provides the benefit of pay-as-you-go, without over-sizing the UPS in the initial phase of datacentre operations. The flexibility of Modulon DPH allows parallel expansion of up to four units to a maximum of 800kW.

Modulon DPH does not compromise on power efficiency performance. Its superior power performance (kVA = kW) and industry-leading AC efficiency (95 per cent at 30 per cent light load and 96 per cent from 50 per cent load) enables customers to save significant energy costs.

Delta Power Solutions (India) Pvt Ltd
www.deltapowersolutions.com

MISCELLANEOUS

Plug-and-place SMT assembly system

Lynx, the new, small form-factor plug-and-place SMT assembly system, is suited for high-mix SMT



production. With 180 feeder lanes on 0.85sqm, it offers the highest feeder density on the market. The system's very high component flexibility is combined with unique capabilities to accurately place 0201 components backed by the latest-generation digital camera, fast laser centering and image processing systems.

With user-friendly Essentec software package, well-proven machine reliability and low maintenance requirement, Lynx ensures steady and reliable flexible production, confirming its motto of Optimise-Operate-Rely.

Essentec AG

Website: www.essentec.com

